

MXRT-2600

3D PCIe Small Form Factor Display Controller



The MXRT-2600 is a high performance 3D PCIe Small Form Factor Display Controller featuring the latest AMD FireProTM 3D technology for leading-edge performance, flexibility and reliability. The board supports DirectX, OpenGL, and OpenCL and is compatible with Microsoft Windows® 7, Windows® 8.1, and Windows® 10.

- Low-Profile MXRT display controller (Low-Profile bracket included)
- 2 GB DDR3 display memory
- Single-wide / low power consumption
- Display Port (DP) 1.2 video outputs
- Powered by AMD's scalable FirePro workstation GPU

Product specifications**MXRT-2600****General specifications**

Bus compatibility	PCIe Gen3 x16
Power consumption	26 W
Form factor	168mm (L) x 68mm (H) single PCIe slot wide
Operating system	Windows 7, 32/64-bit, Windows 8.1 64-bit, Windows 10 64-bit
Platforms	Intel® and AMD architectures
Power Connector	None
Graphics accelerator	ATI FirePro™
Display memory	2 GB DDR3
Memory interface	128-bit
Memory bandwidth	28.8 GB/s
Pixel depth	32-bit pixels (supports 8-bit and 10-bit per color channel)
Electrical standard	Display Port (DP) complying to v1.2
Direct3D hardware support	Microsoft® DirectX v11.2, Vertex Shader 5.0, Pixel Shader 5.0
OpenGL hardware support	OpenGL 4.4
OpenCL hardware support	OpenCL 2.0
Connectors	2-DisplayPort (DP)
Supported resolutions	Up to 5.8MP grayscale at full refresh rate (VGA at boot-up)
Approvals	FCC Part 15 Class B, EN 55022 Limit B, EN 55024, UL-60950-1, BMSI CNS, CISPR-22/24, IEC60950-1, VCCI, CSA C22.2, EU RoHS directive (2011/65/EC), Certificate of Information & Communication Equipment (Republic of Korea), CAN ICES-3(B)/NMB-3(B)
Environmental	Operational temperature: 0° to 55°C
Connectivity	Native DisplayPort suggested Single-link DisplayPort or Dual-link DisplayPort to DVI-I adaptor available separately from Barco

Last updated: 22 Jun 2026

© 2026 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.