F70-4K4

4K laser phosphor projector

- **Up to 4K (3,840 x 2,400) resolution**
- **Durable and robust for 24/7 operation**
- **Improved motion Smear Reduction Processing (SRP)**

The F70-4K4, powered by Barco Pulse image processing, is an addition to the flagship F70 laser-phosphor series with native WQXGA and up to 4K (3,840 x 2,400) resolution. It comes with improved performance for fast moving content, as well as improved color-to-white ratio, intended for high-demanding applications. Designed specifically for the simulation market's tough requirements it is robust and reliable, with an outstanding image quality.

24/7 operation for Low Total Cost of Ownership (TCO)

Designed for the motion platform's rapid and sudden movements, it is the perfect choice for any type of applications that need a robust visual system that last over time and can be operated 24/7. With a lifetime of up to 50,000 hours* coupled with long service intervals, the F70-series is one of the most durable projectors on the market and make sure the training time is maximized.

Optimized for smooth image performance

The F70-4K4's powerful and improved Motion Smear Reduction Processing (SRP) is optimized to remove the typical challenges occurring when viewing fast-moving content, e.g. when an aircraft is rolling, pitching, or banking. Combined with an improved color-to-white ratio, the user will experience increased brightness in colors, better color performance across moving images and deeper black levels for an impeccable reproduction of scenes. The SRP feature will also have a positive impact on lifetime.

With the Constant Light Output (CLO^{TM}) functionality, the projector produces predictable, constant brightness and color over time. And thanks to Barco's unique and proprietary Single Step Processing (SSP^{TM}) technology inherent in Barco Pulse, the F70 can perform several simultaneous processing intensive tasks, like running 4K resolution and warping/blending, without adding extra latency, providing a sharper and higher overall image quality.

*Depending on the mode of operation

Product specificaties	F70-4K4
Algemene specificaties	
Helderheid	3,800 Lumens
Contrastverhouding	1,800 – 6,000:1 sequential
IR voor NVG	no
Uniformiteit van de helderheid	90%
Aspectverhouding	16:10
Type projector	1DLP laser phosphor
Resolutie	3,840 x 2,400 / 3,840 x 2,160 / 2,560 x 1,600 (native)
Type lens	FLD-series
Optische lensverschuiving	Vertical up to 146%, depending on lens Horizontal up to 70%, depending on lens Motorized zoom and focus (+ lens memory FLDX lenses) Motorized lens shift (with position memory on all lenses)
Kleurcorrectie	P7 RealColor™
CLO (constante lichtopbrengst)	Yes
Lichtbron	Laser phosphor
Levensduur lichtbron	Minimum 25,000 hours @ full power Up to 50,000 hours, depending on mode of operation
Verzegelde DLP™ core	Yes
Oriëntatie	360° rotation, no restrictions
3D	Active stereoscopic 3D
Beeldverwerking	Embedded warp & blend engine (Barco Pulse)
Keystone-correctie	Yes
Ingangen	HDSDI 2x DP1.2 2x dual link DVI-I HDBaseT HDMI™ 2.0 (HDCP2.2, HDR10) RJ 45 Ethernet DMX in/out RS232 in 2x USB 12v out
Invoerresolutie	Including and up to: 3,840 x 2,400 @ 60Hz 3,840 x 2,160 @ 60Hz 4,096 x 2,160 @ 60Hz 2,560 x 1,600 @ 120Hz refresh rates: 24Hz to 120Hz for WQXGA (2560x1600) and 24Hz to 60Hz for 4K/4KUHD (4096 x 2160/ 3860 x 2400)
Kleurdiepte invoeren	Up to 12-bit, depending on configuration
Softwaretools	Projector Toolset
Bediening	IR, RS232, RJ45
Netwerkverbinding	IR, RS232, RJ45
Stroomvereisten	100-240V / 50-60Hz
Stroomverbruik	743 W nominal, 1100 W maximum
BTU per uur	Max 4,000 BTU/h
Geluidsniveau (typisch bij 25°C/77°F)	36 dB(A)
Temperatuur tijdens gebruik	10 -40 °C (sea level)
Temperatuur bij opslag	-20 to 60 °C
Luchtvochtigheid tijdens gebruik	20 -80% RH
Luchtvochtigheid bij opslag	10 -90% RH
Afmetingen (B x L x H)	475 x 593 x 286 mm / 18,7 x 23,3 x 11,2 in
Gewicht	37 kg / 81,5 lbs
Standaardaccessoires	Power cord, wireless remote control
Certificeringen	CE, FCC Class A and cNus
Garantie	Limited 5 years parts and labor, extendable

Laatst bijgewerkt: 09 Jul 2026

© 2026 Barco nv. Alle rechten voorbehouden. Gehele of gedeeltelijke reproductie zonder schriftelijke toestemming is verboden. Alle merknamen en productnamen zijn handelsmerken, geregistreerde handelsmerken of handelsnamen van hun respectieve houders. Als gevolg van voortdurende innovatie kunnen informatie en technische specificaties zonder voorafgaande kennisgeving worden gewijzigd. Controleer www.barco.com voor de nieuwste specificaties.