MDDC-2424

diagnostic display built for dental specialists



- **24" diagnostic display for dental imaging**
- **Front sensor for consistent images**
- **Automated calibration & QA**
- **Built-in DIN 6868-157 compliance**
- **Certified medical device, built for dental clinics**

Dental diagnostic reading demands more than a general-purpose monitor can deliver. Reading a panoramic, a cephalometric series, an intraoral study, or a cone beam CT means catching the kind of subtle detail — a hairline root fracture, the earliest shadow of caries, a fine change in bone density — that a generic screen was never built to reveal. MDDC-2424 is designed specifically for that job: a display created so dental specialists and their practices can trust every image they read, in every room, every time.

Confidence in every detail

MDDC-2424 keeps subtle findings visible instead of lost in noise: early caries, periodontal ligament changes, hairline fractures, fine bone structure. The full study is shown in one clear view, without cropping or endless scrolling.

Quality that holds over time

Day-one quality that drifts isn't diagnostic quality. An integrated front-of-screen sensor and QAWeb-managed calibration keep brightness and contrast stable throughout the display's working life — predictable year after year, and uniform from one workstation to the next.

Made for the clinic, not the office

A certified medical device with a housing designed to be cleaned between patients, plus the connectivity and mounting flexibility a real dental workflow needs. It fits into clinical routine rather than complicating it.

Every dental specialty covered

MDDC-2424 supports the specialties that depend on precise imaging:



- Endodontics: gingival tissue, cortical and medullary bone, and root-end depth, with accurate grayscale reproduction.
- Prosthodontics: dependable 3D visualisation of edentulous sites for implant planning.
- Orthodontics: panoramic clarity for implants, impacted teeth, TMJ assessment and orthognathic planning.
- Periodontics: sensitivity to detect alveolar bone level changes and osseous defect architecture.
- Oral & maxillofacial surgery: the detail that reconstruction and extraction planning demand on CBCT.

Quality assurance and compliance, built in

QAWeb Enterprise, Barco's cloud-based QA platform, automates calibration and testing across every workstation — no local server, with audit-ready reporting and enterprise-grade data protection. QAWeb for DIN 6868-157 automates acceptance and consistency testing for both dental room classes the standard defines, with compact reports for straightforward record-keeping.

Specifiche tecniche	MDDC-2424
Specifiche generali	
Tecnologia dello schermo	ADS
Dimensione dello schermo attivo (diagonale)	24"
Dimensioni dello schermo attivo (H x V)	518.4 mm x 324 mm
Rapporto di aspetto (H:V)	16:10
Risoluzione	2 MP (1920 x 1200 pixels @ 60 Hz)
Passo pixel	0.27 mm
Imaging a colori	Yes
Imaging a toni di grigio	Yes
Profondità di bit	8 bit per R, G, B
Angolo di visuale (Orizz., Vert.)	178°
Calibrazione del colore (sRGB)	Yes
Gamut di colore	Refer to panel specification
Sensore frontale (FLOS)	Yes
Luminanza massima (tipica del pannello)	600 cd/m²
Luminanza calibrata DICOM	350 cd/m²
Rapporto di contrasto (tipico del pannello)	1000:1
Tempo di risposta ((Tr + Tf)/2) (tipico)	14 ms
Colore dell'alloggiamento	RAL 9003
Segnali di ingresso video	1x DisplayPort 1x DVI-D 1x DVI-A 1x HDMI
Porte USB	1x USB 2.0 Type-B upstream 2x USB 2.0 Type-A downstream
Valore alimentazione	12 Vdc, 5A
Consumo energetico	< 28 W < 0.3 W (hibernate) < 0.3 W (switched off)
Dimensioni con supporto (L x A x P)	Portrait: 383 x 577.1~629.1 x 201.3 mm Landscape: 568 x 420.6~530.6 x 201.3 mm
Dimensioni senza supporto (L x A x P)	568 x 383 x 67.3 mm
Dimensioni imballaggio (L x A x P)	681 x 512 x 198 mm
Peso netto con supporto	6.8 kg
Peso netto senza supporto	4.6 kg
Peso netto con imballaggio	11.2 kg
Inclinazione	-5° to +22°
Funzione pivot	90°
Gamma di regolazione dell'altezza	110 mm
Standard di montaggio	VESA (100 mm)
Protezione dello schermo	All digital images, except digital mammography.
Certificazioni	CE 0123 (Medical Device) Safety specific: IEC 60601-1:2005 + AMD1:2012+ AMD2:2020 EN 60601-1:2006 + A1:2013 + A12:2014 IEC 62368-1:2018 EN 62368-1:2020 + A11:2020 IEC 60601-1-6:2010 + AMD1:2013 + AMD2:2020 EMC specific: IEC 60601-1-2:2014 + A1:2020 EN 60601-1-2:2015 + A1:2021 Environmental: EU RoHS, REACH, WEEE, Packaging Directive
Accessori in dotazione	1x DisplayPort video cable 1x USB cable 1x Printed user guide (in English, other languages can be found on the documentation disc) 1x Documentation disc 1x System sheet Mains cable Cable cover Cable clamp External power supply
Software di controllo qualità	QAWeb Enterprise, QAWeb for DIN
Garanzia	5 years
Temperatura di esercizio	0°C to +40 °C
Temperatura di stoccaggio	-20 °C to +60 °C
Umidità di esercizio	20 % to 80 % (non-condensing)
Umidità di stoccaggio	10% to 80 %
Pressione minima di esercizio	70 kPa
Pressione di stoccaggio	50 to 106 kPa

Generato il: 06 Nov 2026

© 2026 Barco nv. Tutti i diritti riservati. La riproduzione totale o parziale è proibita in assenza di autorizzazione scritta. Tutti i nomi di marchi e di prodotti sono marchi, marchi registrati o nomi commerciali dei rispettivi proprietari. A causa delle continue innovazioni, le informazioni e le specifiche tecniche sono soggette a modifiche senza preavviso. Controlla www.barco.com per le specifiche più recenti.