

# Runar Cinemascope

0.9 mm Pixel Pitch, Flagship Residential LED Wall



- 0.9 mm pixel pitch
- 5K Cinemascope resolution (5,120 x 2,160)
- 4.80 m wide image (205" diagonal)
- State-of-the-art Micro LED in Package (MIP) technology
- DCI-grade HDR at 300 nits and consumer HDR at 1,000 nits
- Ultra-deep 0.005 cd/m<sup>2</sup> black level
- Full DCI-P3 coverage
- DCI 17:9 aspect (4,096 x 2,160) option available

More than a display, Barco Runar™ is a statement of presence.

Behind minimalist design is extraordinary power, inspired by the quiet strength and elemental purity of the Nordic heritage that inspired it.

Barco Runar combines precision and elegance with technical prowess to create an immersive experience that commands attention without ever raising its voice.

Designed for dedicated home theaters where Cinemascope content shines without black bars, Barco Runar Cinemascope features state-of-the-art Micro LED in Package (MIP) technology and is engineered for future-proof compliance with premium DCI-HDR content.

It delivers breathtaking contrast and color precision, with up to 200,000:1 contrast, ultra-deep 0.005 cd/m<sup>2</sup> black level, and full DCI-P3 coverage.

Engineered for exceptional HDR performance, Runar brings DCI-grade HDR at 300 nits and consumer HDR at 1,000 nits to life with remarkable accuracy, while also handling standard content effortlessly.

Imagine experiencing both DCI-HDR and consumer HDR content on a single LED video wall, seamlessly integrated for your luxury home cinema. Barco Residential makes this a reality.

\*Specifications are preliminary and subject to change.

**技術仕様****RUNAR CINEMASCOPE****一般仕様**

解像度	5K Cinemascope: 5,120 x 2,160 pixels
ピクセルピッチ	0.9 mm
輝度	Up to 1,000 nits
画像処理	16 bit
色深度	12 bit
コントラスト	Up to 200,000:1
HDR	Yes
フレームレート	Up to 120 fps
3D	Yes
寸法 (幅x奥行きx高さ)	4,800 x 2,025 x 75.5 mm / 15.7' x 6.6' x 0.25'
重量	295 kg / 650 lbs
動作湿度	10 -90%
動作温度	-10 °C to + 40 °C / 14 °F to 104 °F
消費電力	Standby: 940W 48nits: 1,130W (max), 990W (typical) 300nits: 1,750W (max), 1,140W (typical) 500nits: 2,130W (max), 1,240W (typical) 1,000nits: 3,250W (max), 1,520W (typical)
BTU/時	Standby: 3,210 BTU/h 48nits: 3,860 BTU/h (max), 3,380 BTU/h (typical) 300nits: 5,970 BTU/h (max), 3,860 BTU/h (typical) 500nits: 7,270 BTU/h (max), 4,230 BTU/h (typical) 1,000nits: 11,090 BTU/h (max), 5,190 BTU/h (typical)
電源要件	AC110V 15Ax2 or AC220V 8Ax2
証明書	Scheduled for DCI HDR certificate
Inputs	HDMI 2.1 (up to 4K 120p 444 10bit) 2D up to 4K 120fps (DCI SDR/HDR) 3D up to 4K 24/48/60fps per eye (DCI SDR/HDR) Bitrate 1,250 Mbps
Audio	AES3, 16ch 48/96KHz, 24bit, 2xRJ45
保証	3 years (Expandable to 5 years)

生成日:21 May 2026

© 2026 Barco nv.(C) Barco. All rights reserved. (無断転載を禁ず。) 書面による許可なく全部または一部を複製することは禁止されています。すべてのブランド名および製品名は、それぞれの所有者の商標、登録商標、または商号です。継続的な技術革新により、情報および技術仕様は予告なく変更される場合があります。最新の仕様についてはwww.barco.comをご確認ください。