MDDC-2424

diagnostic display built for dental specialists



- **24" diagnostic display for dental imaging**
- **Front sensor for consistent images**
- **Automated calibration & QA**
- **Built-in DIN 6868-157 compliance**
- **Certified medical device, built for dental clinics**

Dental diagnostic reading demands more than a general-purpose monitor can deliver. Reading a panoramic, a cephalometric series, an intraoral study, or a cone beam CT means catching the kind of subtle detail — a hairline root fracture, the earliest shadow of caries, a fine change in bone density — that a generic screen was never built to reveal. MDDC-2424 is designed specifically for that job: a display created so dental specialists and their practices can trust every image they read, in every room, every time.

Confidence in every detail

MDDC-2424 keeps subtle findings visible instead of lost in noise: early caries, periodontal ligament changes, hairline fractures, fine bone structure. The full study is shown in one clear view, without cropping or endless scrolling.

Quality that holds over time

Day-one quality that drifts isn't diagnostic quality. An integrated front-of-screen sensor and QAWeb-managed calibration keep brightness and contrast stable throughout the display's working life — predictable year after year, and uniform from one workstation to the next.

Made for the clinic, not the office

A certified medical device with a housing designed to be cleaned between patients, plus the connectivity and mounting flexibility a real dental workflow needs. It fits into clinical routine rather than complicating it.

Every dental specialty covered

MDDC-2424 supports the specialties that depend on precise imaging:



- Endodontics: gingival tissue, cortical and medullary bone, and root-end depth, with accurate grayscale reproduction.
- Prosthodontics: dependable 3D visualisation of edentulous sites for implant planning.
- Orthodontics: panoramic clarity for implants, impacted teeth, TMJ assessment and orthognathic planning.
- Periodontics: sensitivity to detect alveolar bone level changes and osseous defect architecture.
- Oral & maxillofacial surgery: the detail that reconstruction and extraction planning demand on CBCT.

Quality assurance and compliance, built in

QAWeb Enterprise, Barco's cloud-based QA platform, automates calibration and testing across every workstation — no local server, with audit-ready reporting and enterprise-grade data protection. QAWeb for DIN 6868-157 automates acceptance and consistency testing for both dental room classes the standard defines, with compact reports for straightforward record-keeping.

Product specificaties	MDDC-2424
Algemene specificaties	
Schermtechnologie	ADS
Actieve schermgrootte (diagonaal)	24"
Actieve schermgrootte (H x V)	518.4 mm x 324 mm
Beeldverhouding (H:V)	16:10
Resolutie	2 MP (1920 x 1200 pixels @ 60 Hz)
Pixelpitch	0.27 mm
Kleurenbeeld	Yes
Grijze beeldvorming	Yes
Bitdiepte	8 bit per R, G, B
Kijkhoek (H, V)	178°
Kleurenkalibratie(sRGB)	Yes
Kleurengamma	Refer to panel specification
Sensor aan de voorkant (FLOS)	Yes
Maximale luminance (afhankelijk van het paneel)	600 cd/m²
DICOM gekalibreerde luminantie	350 cd/m²
Contrastverhouding (afhankelijk van het paneel)	1000:1
Reactietijd ((Tr + Tf)/2) (normaal)	14 ms
Kleur behuizing	RAL 9003
Video-ingangssignalen	1x DisplayPort 1x DVI-D 1x DVI-A 1x HDMI
USB-poorten	1x USB 2.0 Type-B upstream 2x USB 2.0 Type-A downstream
Nominaal vermogen	12 Vdc, 5A
Stroomverbruik	< 28 W < 0.3 W (hibernate) < 0.3 W (switched off)
Afmetingen met standaard (B x H x D)	Portrait: 383 x 577.1~629.1 x 201.3 mm Landscape: 568 x 420.6~530.6 x 201.3 mm
Afmetingen zonder standaard (B x H x D)	568 x 383 x 67.3 mm
Afmetingen verpakt (B x H x D)	681 x 512 x 198 mm
Nettogewicht met standaard	6.8 kg
Nettogewicht zonder standaard	4.6 kg
Netto gewicht verpakt	11.2 kg
Kanteling	-5° to +22°
Scharnieren	90°
Hoogteregelbereik	110 mm
Montagestandaard	VESA (100 mm)
Scherm Bescherming	All digital images, except digital mammography.
Certificeringen	CE 0123 (Medical Device) Safety specific: IEC 60601-1:2005 + AMD1:2012+ AMD2:2020 EN 60601-1:2006 + A1:2013 + A12:2014 IEC 62368-1:2018 EN 62368-1:2020 + A11:2020 IEC 60601-1-6:2010 + AMD1:2013 + AMD2:2020 EMC specific: IEC 60601-1-2:2014 + A1:2020 EN 60601-1-2:2015 + A1:2021 Environmental: EU RoHS, REACH, WEEE, Packaging Directive
Meegeleverde accessoires	1x DisplayPort video cable 1x USB cable 1x Printed user guide (in English, other languages can be found on the documentation disc) 1x Documentation disc 1x System sheet Mains cable Cable cover Cable clamp External power supply
QA-software	QAWeb Enterprise, QAWeb for DIN
Garantie	5 years
Temperatuur tijdens gebruik	0°C to +40 °C
Opslagtemperatuur	-20 °C to +60 °C
Luchtvochtigheid tijdens gebruik	20 % to 80 % (non-condensing)
Luchtvochtigheid bij opslag	10% to 80 %
Minimum bedrijfsdruk	70 kPa
Opslagdruk	50 to 106 kPa

Laatst bijgewerkt: 06 Nov 2026

© 2026 Barco nv. Alle rechten voorbehouden. Gehele of gedeeltelijke reproductie zonder schriftelijke toestemming is verboden. Alle merknamen en productnamen zijn handelsmerken, geregistreerde handelsmerken of handelsnamen van hun respectieve houders. Als gevolg van voortdurende innovatie kunnen informatie en technische specificaties zonder voorafgaande kennisgeving worden gewijzigd. Controleer www.barco.com voor de nieuwste specificaties.