

Runar

0.9 mm Pixel Pitch, Flagship Residential LED Wall



- 0.9 mm pixel pitch
- Native DCI 4K resolution (4,096 x 2,160)
- 3.84 m wide image (171" diagonal)
- State-of-the-art Micro LED in Package (MIP) technology
- DCI-grade HDR at 300 nits and consumer HDR at 1,000 nits
- Ultra-deep 0.005 cd/m² black level
- Full DCI-P3 coverage
- Cinemascope aspect (5, 120 x 2,160) option available

More than a display, Barco Runar™ is a statement of presence. Behind minimalist design is extraordinary power, inspired by the quiet strength and elemental purity of the Nordic heritage that inspired it. Barco Runar combines precision and elegance with technical prowess to create an immersive experience that commands attention without ever raising its voice.

Barco Runar features state-of-the-art Micro LED in Package (MIP) technology and is engineered for future-proof compliance with premium DCI-HDR content. It delivers breathtaking contrast and color precision, with up to 200,000:1 contrast, ultra-deep 0.005 cd/m² black level, and full DCI-P3 coverage. Engineered for exceptional HDR performance, Runar brings DCI-grade HDR at 300 nits and consumer HDR at 1,000 nits to life with remarkable accuracy, while also handling standard content effortlessly.

Imagine experiencing both DCI-HDR and consumer HDR content on a single LED video wall, seamlessly integrated for your luxury home cinema. Barco Residential makes this a reality.

*Specifications are preliminary and subject to change.

Технические характеристики**RUNAR****Общие технические характеристики**

Разрешение	Native DCI 4K: 4,096 x 2,160 pixels
Шаг пикселей	0.9 mm
Яркость	Up to 1,000 nits
Обработка изображений	16 bit
Глубина цвета	12 bit
Контраст	Up to 200,000:1
HDR	Yes
Частота кадров	Up to 120 fps
3D	Yes
Размеры (ШxДxВ)	3,840 x 2,025 x 75.5 mm / 12.6' x 6.6' x 0.25'
Вес	235 kg / 518 lbs
Влажность воздуха при эксплуатации	10 -90%
Рабочая температура	-10 °C to + 40 °C / 14 °F to 104 °F
Потребляемая мощность	Standby: 750W 48nits: 900W (max), 790W (typical) 300nits: 1,400W (max), 910W (typical) 500nits: 1,700W (max), 990W (typical) 1,000nits: 2,600W (max), 1,210W (typical)
БТЕ в час	Standby: 2,560 BTU/h 48nits: 3,070 BTU/h (max), 2,700 BTU/h (typical) 300nits: 4,780 BTU/h (max), 3,110 BTU/h (typical) 500nits: 5,800 BTU/h (max), 3,380 BTU/h (typical) 1,000nits: 8,870 BTU/h (max), 4,130 BTU/h (typical)
Требования к питанию	AC110V 15Ax2 or AC220V 8Ax2
Сертификаты	Scheduled for DCI HDR certificate
Inputs	HDMI 2.1 (up to 4K 120p 444 10bit) 2D up to 4K 120fps (DCI SDR/HDR) 3D up to 4K 24/48/60fps per eye (DCI SDR/HDR) Bitrate 1,250 Mbps
Audio	AES3, 16ch 48/96KHz, 24bit, 2xRJ45
Гарантия	3 years (Expandable to 5 years)

Создано: 21 May 2026

© 2026 Барко нв. Все права защищены. Полное или частичное воспроизведение без письменного разрешения запрещено. Все названия брендов и продуктов являются товарными знаками, зарегистрированными товарными знаками или торговыми наименованиями соответствующих владельцев. В связи с непрерывными обновлениями информация и технические характеристики могут меняться без предварительного уведомления. Пожалуйста, проверьте www.barco.com для получения последних спецификаций.

www.barco.com

