DisplayPort 1.2 Quad output card



- Four DisplayPort 1.2 connectors
- Supports up to 4x 1600p@60, or 2x 4K@60p/ UHD per card (single cable)
- HDCP 1.4 compliant
- Support for VESA/CEA, and custom timings
- Automatic output acquisition and configuration

Product specifications	DISPLAYPORT 1.2 QUAD OUTPUT CARD
General Specifications	
Connectors	4x full sized DisplayPort connectors
Resolution	up to 2x 4096x2160@60p
Color depth	8-bit; 10-bit; 12-bit (DL or lower)
Features	Rotation and splitter mode
Color sampling	up to UHD@60p 4:4:4 10-bit
HDCP	HDCP 1.x compliant
Signal capacity	660 MHz
Specifications when used with Encore3	
Connectors*	4x full sized DisplayPort connectors
Resolution*	Support up to 4x 4096x2160 @60Hz
Color depth*	8-bit; 10-bit; 12-bit
Color sampling*	up to UHD@60p 4:4:4 10-bit
HDCP*	HDCP 1.x compliant (top two connectors)
Signal capacity*	up to 4096x2160 @60Hz
*Specifications when used with Encore3	

Last updated: 17 Nov 2026

© 2026 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.