MDDC-2424

diagnostic display built for dental specialists



- **24" diagnostic display for dental imaging**
- **Front sensor for consistent images**
- **Automated calibration & QA**
- **Built-in DIN 6868-157 compliance**
- **Certified medical device, built for dental clinics**

Dental diagnostic reading demands more than a general-purpose monitor can deliver. Reading a panoramic, a cephalometric series, an intraoral study, or a cone beam CT means catching the kind of subtle detail — a hairline root fracture, the earliest shadow of caries, a fine change in bone density — that a generic screen was never built to reveal. MDDC-2424 is designed specifically for that job: a display created so dental specialists and their practices can trust every image they read, in every room, every time.

Confidence in every detail

MDDC-2424 keeps subtle findings visible instead of lost in noise: early caries, periodontal ligament changes, hairline fractures, fine bone structure. The full study is shown in one clear view, without cropping or endless scrolling.

Quality that holds over time

Day-one quality that drifts isn't diagnostic quality. An integrated front-of-screen sensor and QAWeb-managed calibration keep brightness and contrast stable throughout the display's working life — predictable year after year, and uniform from one workstation to the next.

Made for the clinic, not the office

A certified medical device with a housing designed to be cleaned between patients, plus the connectivity and mounting flexibility a real dental workflow needs. It fits into clinical routine rather than complicating it.

Every dental specialty covered

MDDC-2424 supports the specialties that depend on precise imaging:



- Endodontics: gingival tissue, cortical and medullary bone, and root-end depth, with accurate grayscale reproduction.
- Prosthodontics: dependable 3D visualisation of edentulous sites for implant planning.
- Orthodontics: panoramic clarity for implants, impacted teeth, TMJ assessment and orthognathic planning.
- Periodontics: sensitivity to detect alveolar bone level changes and osseous defect architecture.
- Oral & maxillofacial surgery: the detail that reconstruction and extraction planning demand on CBCT.

Quality assurance and compliance, built in

QAWeb Enterprise, Barco's cloud-based QA platform, automates calibration and testing across every workstation — no local server, with audit-ready reporting and enterprise-grade data protection. QAWeb for DIN 6868-157 automates acceptance and consistency testing for both dental room classes the standard defines, with compact reports for straightforward record-keeping.

Spécifications techniques — MDDC-2424

Spécifications générales

Technologie d'écran	ADS
Taille de l'écran actif (diagonale)	24"
Taille de l'écran actif (H x V)	518.4 mm x 324 mm
Rapport d'aspect (H:V)	16:10
Résolution	2 MP (1920 x 1200 pixels @ 60 Hz)
Pas de pixels	0.27 mm
Imagerie couleur	Yes
Imagerie grise	Yes
Profondeur de bits	8 bit per R, G, B
Angle de vision (H, V)	178°
Calibrage des couleurs (sRGB)	Yes
Gamme de couleurs	Refer to panel specification
Capteur avant (FLOS)	Yes
Luminance maximale (panneau typique)	600 cd/m²
Luminance calibrée DICOM	350 cd/m²
Rapport de contraste (panneau typique)	1000:1
Temps de réponse ((Tr + Tf)/2) (typique)	14 ms
Couleur du boîtier	RAL 9003
Signaux d'entrée vidéo	1x DisplayPort 1x DVI-D 1x DVI-A 1x HDMI
Ports USB	1x USB 2.0 Type-B upstream 2x USB 2.0 Type-A downstream
Puissance nominale	12 Vdc, 5A
Consommation électrique	< 28 W < 0.3 W (hibernate) < 0.3 W (switched off)
Dimensions avec support (L x H x P)	Portrait: 383 x 577.1~629.1 x 201.3 mm Landscape: 568 x 420.6~530.6 x 201.3 mm
Dimensions sans support (L x H x P)	568 x 383 x 67.3 mm
Dimensions emballé (l x H x P)	681 x 512 x 198 mm
Poids net avec support	6.8 kg
Poids net sans support	4.6 kg
Poids net emballé	11.2 kg
Inclinaison	-5° to +22°
Pivot	90°
Plage de réglage de la hauteur	110 mm
Norme de montage	VESA (100 mm)
Protection d'écran	All digital images, except digital mammography.
Certifications	CE 0123 (Medical Device) Safety specific: IEC 60601-1:2005 + AMD1:2012+ AMD2:2020 EN 60601-1:2006 + A1:2013 + A12:2014 IEC 62368-1:2018 EN 62368-1:2020 + A11:2020 IEC 60601-1-6:2010 + AMD1:2013 + AMD2:2020 EMC specific: IEC 60601-1-2:2014 + A1:2020 EN 60601-1-2:2015 + A1:2021 Environmental: EU RoHS, REACH, WEEE, Packaging Directive
Accessoires fournis	1x DisplayPort video cable 1x USB cable 1x Printed user guide (in English, other languages can be found on the documentation disc) 1x Documentation disc 1x System sheet Mains cable Cable cover Cable clamp External power supply
Logiciel d'assurance qualité	QAWeb Enterprise, QAWeb for DIN
Garantie	5 years
Température de fonctionnement	0°C to +40 °C
Température de stockage	-20 °C to +60 °C
Humidité de fonctionnement	20 % to 80 % (non-condensing)
Humidité de stockage	10% to 80 %
Pression minimale de fonctionnement	70 kPa
Pression de stockage	50 to 106 kPa

Crée le : 06 Nov 2026

© 2026 Barco nv. Tous droits réservés. La reproduction partielle ou intégrale sans autorisation écrite préalable est interdite. Les noms de marques ou de produits sont des marques commerciales, des marques déposées ou des appellations commerciales appartenant à leurs détenteurs respectifs. Pour des raisons d'innovation continue, les informations et les caractéristiques techniques sont susceptibles d'être modifiées sans préavis. Veuillez consulter www.barco.com pour les dernières spécifications.