

# MXRT-5600

3D PCIe 4-head mid-range display controller



With the high-performance MXRT-5600 display controller, you can drive up to four monitors with just one PCIe slot. This makes it a perfect match for PACS workstations combining two diagnostic displays with additional displays for patient lists or 3D viewing applications. The MXRT-5600 is compatible with the DisplayPort interface standard, which assures easy installation and ultra-fast and reliable data transfers.

- 4 display outputs
- PCIe 3.0 compliant
- 4 GB GDDR5 display memory
- Single-wide form factor
- DisplayPort (DP) 1.2 video outputs
- Powered by AMD's scalable FirePro workstation GPU

**Product specifications****MXRT-5600****General specifications**

Bus compatibility	PCIe Gen3 x16
Power consumption	75 W
Form factor	184.15 mm (7.2") (L) x 111 mm (4.4") (H) single PCIe slot wide
Operating system	Windows 7 -32/64-bit, Windows 8.1 64-bit, Windows 10 64-bit
Platforms	Intel® and AMD architectures
Graphics accelerator	ATI FirePro TM
Display memory	4 GB GDDR5
Memory interface	128-bit
Memory bandwidth	96 GB/s
Pixel depth	32-bit pixels (supports 8-bit and 10-bit per color channel)
Electrical standard	DisplayPort (DP) complying to v1.2
Direct3D hardware support	Microsoft® DirectX v11.2, Vertex Shader 5.0, Pixel Shader 5.0
OpenGL hardware support	OpenGL 4.4
OpenCL hardware support	OpenCL 2.0
Connectors	4-DisplayPort (DP)
Supported resolutions	Up to 5.8MP color/gray at full refresh rate (VGA at boot-up)
Approvals and compliance	FCC Part 15 Class B, EN 55022 Limit B, EN 55024, UL-60950-1, BMSI CNS, CISPR-22/24, IEC60950-1, VCCI, CSA C22.2, EU RoHS directive (2011/65/EC), Certificate of Information & Communication Equipment (Republic of Korea), CAN ICES-3(B)/NMB-3(B)
Operational temperature	0° to 45°C
Connectivity	Native DisplayPort suggested  Single-link DisplayPort or Dual-link DisplayPort to DVI-I adaptor available separately from Barco

Last updated: 22 Jun 2026

© 2026 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check [www.barco.com](http://www.barco.com) for the latest specifications.