

MNA-240 DP 1.2 SST Encoder

4K AV-to-IP adapter for the OR and hybrid OR



- AV-to-IP conversion
- Up to 4K resolution
- Medical-grade

Adapter for the operating room

The MNA-240 DP 1.2 encoder converts DisplayPort video signals to Nexxis RAW IP packets. Other non-video signals such as audio and USB for keyboard/mouse are also supported. End-to-end video latency is amazingly short and is guaranteed not to exceed a single frame. The video streams that are distributed over the Nexxis network can go up to a resolution of 4K.

Capabilities

- AV-to-IP conversion at the source
- Seamless integration in the Nexxis environment
- Support for non-video traffic (e.g. keyboard, mouse and audio) via USB and audio connections
- Easy integration via central API provided by the Nexxis OR Management Suite NMS
- Streaming of 4K and downscaled FHD video onto the network

The MNA-240 adapters are part of Barco's Nexxis solution, which provides users with uncompromised networked visualization for the digital operating room. The compact Nexxis AV-to-IP adapters offer simplicity and flexibility while maintaining the highest possible performance standards and fitness for use in demanding medical environments.

Product specificaties**MNA-240 DP 1.2 SST ENCODER****Algemene specificaties**

Videoconversie	Converts Digital video signals to uncompressed IP streams
Verwerking	Up to 4096x2160@60
Kleurdiepte	RGB24 8-bit; YCbCr 4:2:0 (8-bit & 10-bit) ; YCbCr 4:2:2 (8-bit & 10-bit); YCbCr 4:4:4 (8-bit)
Latentie	Subframe
Beveiliging	AES 128 encryption of all video, data & control signals
Encodersysteem	N/A
Video-uitvoer	N/A
Video-invoer	Interface: 1x DP 1.2 SST
Netwerkuitgang	1x 4K/UHD uncompressed IP stream 1x downscaled FHD IP stream of native 4K/UHD source
IP-connectiviteit	2x 10GbE Fiber Optic Interface with SFP+ module
IP-standaarden	Zeroconf, IPv4, IGMP, DHCP, RTP, RTCP, 802.1q, AES 128b, HTTP(s)
USB	1x micro-USB 2.0 + 3x USB 2.0 type-A
USB Power Output	Max. 5 V / 500 mA (2.5 W) per USB 2.0 Type-A port
Audio	Line-in, line-out, headphones-out and mic-in (mono) 3.5mm connector
Naleving	N/A
GPIO	Trigger via any audio connector via 15mm length compatible 3.5mm TRRS jack
Nexxis Integratie	Supported from Nexxis R1.08 onwards
NexxisPlus-integratie	N/A
PSU	External 12V Medical Approved PSU, 100-240VAC 60W, external locking
Stroomverbruik	< 35 W
Grootte	38 mm H x 170 mm W x 170 mm D 1.5" H x 6.7" W x 6.7" (+/-2mm / 0.1")
Gewicht	1±0.01kg (2.20lbs)
Temperatuur	Operating: 0°C to 40°C (32°F to 104°F)
Vochtigheid	Max 85%
Hoogte	700 hPa
Opslagvoorwaarden	Storage temperature: -20°C to 60°C (-4°F to 140°F) Storage relative humidity: 10% to 93% Storage altitude: 500 hPa
Akoestisch geluidsniveau	Typical 32dBA at 20°C at 1m
Montage	Optional VESA adapter plate or 1U rack mount for 2 devices
Certificeringen	-CB (IEC 60601-1) -CB (IEC 62368-1) -cRU, RU (cRUus) -Demko -CE medical device class I -UKCA -BIS Registration, IS 13252 (part 1)
Normen	Medical Equipment: -IEC 60601-1:2005 + A1:2012 + A2:2020 -IEC 60601-1-6:2010 + A1:2013 + A2:2020 -IEC 60601-1-2:2014+A1:2020 (Ed.4.1) -AAMI ES 60601-1:2005 + A1:2012 + A2:2021 -CAN/CSA-C22.2 No.60601-1:08 + A1:14 (Reaffirmed 2022) -EN 60601-1:2006 + A1:2013 + A12:2014 + A2:2021 + A13:2024 -EN 60601-1-6:2010 + A1:2015 + A2:2021 -EN 60601-1-2:2015+A1:2021 (Ed.4.1) -FCC class B -ICES-001 Level B ITE Equipment: -IEC 62368-1:2018 -EN IEC 62368-1:2020 + A1:2020 -IS 13252 (Part1): 2010
Ondersteuning voor 3D-video	N/A
Streamback	N/A

Laatst bijgewerkt: 31 Mar 2026

© 2026 Barco nv. Alle rechten voorbehouden. Gehele of gedeeltelijke reproductie zonder schriftelijke toestemming is verboden. Alle merknamen en productnamen zijn handelsmerken, geregistreerde handelsmerken of handelsnamen van hun respectieve houders. Als gevolg van voortdurende innovatie kunnen informatie en technische specificaties zonder voorafgaande kennisgeving worden gewijzigd. Controleer www.barco.com voor de nieuwste specificaties.