MDDC-2424

diagnostic display built for dental specialists



- **24" diagnostic display for dental imaging**
- **Front sensor for consistent images**
- **Automated calibration & QA**
- **Built-in DIN 6868-157 compliance**
- **Certified medical device, built for dental clinics**

Dental diagnostic reading demands more than a general-purpose monitor can deliver. Reading a panoramic, a cephalometric series, an intraoral study, or a cone beam CT means catching the kind of subtle detail — a hairline root fracture, the earliest shadow of caries, a fine change in bone density — that a generic screen was never built to reveal. MDDC-2424 is designed specifically for that job: a display created so dental specialists and their practices can trust every image they read, in every room, every time.

Confidence in every detail

MDDC-2424 keeps subtle findings visible instead of lost in noise: early caries, periodontal ligament changes, hairline fractures, fine bone structure. The full study is shown in one clear view, without cropping or endless scrolling.

Quality that holds over time

Day-one quality that drifts isn't diagnostic quality. An integrated front-of-screen sensor and QAWeb-managed calibration keep brightness and contrast stable throughout the display's working life — predictable year after year, and uniform from one workstation to the next.

Made for the clinic, not the office

A certified medical device with a housing designed to be cleaned between patients, plus the connectivity and mounting flexibility a real dental workflow needs. It fits into clinical routine rather than complicating it.

Every dental specialty covered

MDDC-2424 supports the specialties that depend on precise imaging:



- Endodontics: gingival tissue, cortical and medullary bone, and root-end depth, with accurate grayscale reproduction.
- Prosthodontics: dependable 3D visualisation of edentulous sites for implant planning.
- Orthodontics: panoramic clarity for implants, impacted teeth, TMJ assessment and orthognathic planning.
- Periodontics: sensitivity to detect alveolar bone level changes and osseous defect architecture.
- Oral & maxillofacial surgery: the detail that reconstruction and extraction planning demand on CBCT.

Quality assurance and compliance, built in

QAWeb Enterprise, Barco's cloud-based QA platform, automates calibration and testing across every workstation — no local server, with audit-ready reporting and enterprise-grade data protection. QAWeb for DIN 6868-157 automates acceptance and consistency testing for both dental room classes the standard defines, with compact reports for straightforward record-keeping.

Especificaciones del producto MDDC-2424

Especificaciones generales

Tecnología de pantalla	ADS
Tamaño de la pantalla activa (diagonal)	24"
Tamaño de la pantalla activa (H x V)	518.4 mm x 324 mm
Relación de aspecto (H:V)	16:10
Resolución	2 MP (1920 x 1200 pixels @ 60 Hz)
Profundidad de píxel	0.27 mm
Imágenes en color	Yes
Imágenes en escala de grises	Yes
Profundidad de bits	8 bit per R, G, B
Ángulo de visión (H, V)	178°
Calibración de color (sRGB)	Yes
Gama de colores	Refer to panel specification
Sensor frontal (FLOS)	Yes
Luminancia máxima (típica del panel)	600 cd/m²
Luminancia calibrada DICOM	350 cd/m²
Relación de contraste (típica de panel)	1000:1
Tiempo de respuesta ((Tr + Tf)/2) (típico)	14 ms
Color de la carcasa	RAL 9003
Señales de entrada de vídeo	1x DisplayPort 1x DVI-D 1x DVI-A 1x HDMI
Puertos USB	1x USB 2.0 Type-B upstream 2x USB 2.0 Type-A downstream
Potencia nominal	12 Vdc, 5A
Consumo de energía	< 28 W < 0.3 W (hibernate) < 0.3 W (switched off)
Dimensiones con soporte (ancho x alto x profundidad)	Portrait: 383 x 577.1~629.1 x 201.3 mm Landscape: 568 x 420.6~530.6 x 201.3 mm
Dimensiones sin soporte (ancho x alto x profundidad)	568 x 383 x 67.3 mm
Dimensiones con embalaje (An. x Al. x Pr.)	681 x 512 x 198 mm
Peso neto con soporte	6.8 kg
Peso neto sin soporte	4.6 kg
Peso neto con embalaje	11.2 kg
Inclinación	-5° to +22°
Giro	90°
Rango de ajuste de altura	110 mm
Estándar de montaje	VESA (100 mm)
Protección de pantalla	All digital images, except digital mammography.
Certificaciones	CE 0123 (Medical Device) Safety specific: IEC 60601-1:2005 + AMD1:2012+ AMD2:2020 EN 60601-1:2006 + A1:2013 + A12:2014 IEC 62368-1:2018 EN 62368-1:2020 + A11:2020 IEC 60601-1-6:2010 + AMD1:2013 + AMD2:2020 EMC specific: IEC 60601-1-2:2014 + A1:2020 EN 60601-1-2:2015 + A1:2021 Environmental: EU RoHS, REACH, WEEE, Packaging Directive
Accesorios suministrados	1x DisplayPort video cable 1x USB cable 1x Printed user guide (in English, other languages can be found on the documentation disc) 1x Documentation disc 1x System sheet Mains cable Cable cover Cable clamp External power supply
Software de aseguramiento de la calidad	QAWeb Enterprise, QAWeb for DIN
Garantía	5 years
Temperatura de funcionamiento	0°C to +40 °C
Temperatura de almacenamiento	-20 °C to +60 °C
Humedad de funcionamiento	20 % to 80 % (non-condensing)
Humedad de almacenamiento	10% to 80 %
Presión mínima operativa	70 kPa
Presión de almacenamiento	50 to 106 kPa

Generado en: 06 Nov 2026

© 2026 Barco nv. Todos los derechos reservados. Prohibida la reproducción total o parcial sin autorización por escrito. Todos los nombres de marcas y de productos son marcas comerciales, marcas comerciales registradas o nombres comerciales de sus respectivos titulares. Debido a la innovación continua, la información y las especificaciones técnicas están sujetas a cambios sin previa notificación. Consulta www.barco.com para ver las especificaciones más recientes.