MDDC-2424

diagnostic display built for dental specialists



- **24" diagnostic display for dental imaging**
- **Front sensor for consistent images**
- **Automated calibration & QA**
- **Built-in DIN 6868-157 compliance**
- **Certified medical device, built for dental clinics**

Dental diagnostic reading demands more than a general-purpose monitor can deliver. Reading a panoramic, a cephalometric series, an intraoral study, or a cone beam CT means catching the kind of subtle detail — a hairline root fracture, the earliest shadow of caries, a fine change in bone density — that a generic screen was never built to reveal. MDDC-2424 is designed specifically for that job: a display created so dental specialists and their practices can trust every image they read, in every room, every time.

Confidence in every detail

MDDC-2424 keeps subtle findings visible instead of lost in noise: early caries, periodontal ligament changes, hairline fractures, fine bone structure. The full study is shown in one clear view, without cropping or endless scrolling.

Quality that holds over time

Day-one quality that drifts isn't diagnostic quality. An integrated front-of-screen sensor and QAWeb-managed calibration keep brightness and contrast stable throughout the display's working life — predictable year after year, and uniform from one workstation to the next.

Made for the clinic, not the office

A certified medical device with a housing designed to be cleaned between patients, plus the connectivity and mounting flexibility a real dental workflow needs. It fits into clinical routine rather than complicating it.

Every dental specialty covered

MDDC-2424 supports the specialties that depend on precise imaging:



- Endodontics: gingival tissue, cortical and medullary bone, and root-end depth, with accurate grayscale reproduction.
- Prosthodontics: dependable 3D visualisation of edentulous sites for implant planning.
- Orthodontics: panoramic clarity for implants, impacted teeth, TMJ assessment and orthognathic planning.
- Periodontics: sensitivity to detect alveolar bone level changes and osseous defect architecture.
- Oral & maxillofacial surgery: the detail that reconstruction and extraction planning demand on CBCT.

Quality assurance and compliance, built in

QAWeb Enterprise, Barco's cloud-based QA platform, automates calibration and testing across every workstation — no local server, with audit-ready reporting and enterprise-grade data protection. QAWeb for DIN 6868-157 automates acceptance and consistency testing for both dental room classes the standard defines, with compact reports for straightforward record-keeping.

Especificações técnicas — MDDC-2424

Especificações gerais

Tecnologia de tela	ADS
Tamanho de tela ativo (diagonal)	24"
Tamanho de tela ativa (H x V)	518.4 mm x 324 mm
Proporção de aspecto (H:V)	16:10
Resolução	2 MP (1920 x 1200 pixels @ 60 Hz)
Distância entre pontos	0.27 mm
Imagem a cores	Yes
Imagem cinza	Yes
Profundidade de bits	8 bit per R, G, B
Ângulo de visão (H, V)	178°
Calibração de cor (sRGB)	Yes
Gama de cores	Refer to panel specification
Sensor frontal (FLOS)	Yes
Luminância máxima (painel típico)	600 cd/m²
Luminância calibrada DICOM	350 cd/m²
Taxa de contraste (típica do painel)	1000:1
Tempo de resposta ((Tr + Tf)/2) (típico)	14 ms
Cor da carcaça	RAL 9003
Sinais de entrada de vídeo	1x DisplayPort 1x DVI-D 1x DVI-A 1x HDMI
Portas USB	1x USB 2.0 Type-B upstream 2x USB 2.0 Type-A downstream
Classificação elétrica	12 Vdc, 5A
Consumo de energia	< 28 W < 0.3 W (hibernate) < 0.3 W (switched off)
Dimensões com suporte (L x A x P)	Portrait: 383 x 577.1~629.1 x 201.3 mm Landscape: 568 x 420.6~530.6 x 201.3 mm
Dimensões sem base (L x A x P)	568 x 383 x 67.3 mm
Dimensões da embalagem (L x A x P)	681 x 512 x 198 mm
Peso líquido com suporte	6.8 kg
Peso líquido sem base	4.6 kg
Peso líquido na embalagem	11.2 kg
Inclinação	-5° to +22°
Pivô	90°
Faixa de ajuste de altura	110 mm
Padrão de montagem	VESA (100 mm)
Proteção de tela	All digital images, except digital mammography.
Certificações	CE 0123 (Medical Device) Safety specific: IEC 60601-1:2005 + AMD1:2012+ AMD2:2020 EN 60601-1:2006 + A1:2013 + A12:2014 IEC 62368-1:2018 EN 62368-1:2020 + A11:2020 IEC 60601-1-6:2010 + AMD1:2013 + AMD2:2020 EMC specific: IEC 60601-1-2:2014 + A1:2020 EN 60601-1-2:2015 + A1:2021 Environmental: EU RoHS, REACH, WEEE, Packaging Directive
Acessórios fornecidos	1x DisplayPort video cable 1x USB cable 1x Printed user guide (in English, other languages can be found on the documentation disc) 1x Documentation disc 1x System sheet Mains cable Cable cover Cable clamp External power supply
Software do controle de qualidade	QAWeb Enterprise, QAWeb for DIN
Garantia	5 years
Temperatura de operação	0°C to +40 °C
Temperatura de armazenamento	-20 °C to +60 °C
Umidade de operação	20 % to 80 % (non-condensing)
Umidade de armazenamento	10% to 80 %
Pressão operacional mínima	70 kPa
Pressão de armazenamento	50 to 106 kPa

Gerada em: 06 Nov 2026

© 2026 Barco nv. Todos os direitos reservados. A reprodução total ou parcial sem permissão por escrito é proibida. Todos os nomes de marca e produto são marcas comerciais, marcas comerciais registradas ou nomes dos respectivos proprietários. Por causa da inovação contínua, as informações e as especificações técnicas estão sujeitas a alterações sem aviso prévio. Verifique www.barco.com para obter as especificações mais recentes.