

Infinipix® manager NM100

Infinipix® management software for LED displays



- **Straightforward GUI**
- **Maximum security for data-critical environments**
- **Certified inhouse software development**

The Infinipix® Manager (NM100) is the next generation in LED display management software. The NM100 hosts a straightforward web interface that allows you to access information for your display hardware and offers the tools to (pre)view lay-outs and manipulate settings on the LED wall.

A worry-free canvas

The Infinipix® NM100 allows for stress-free remote serviceability and makes the life of any installer or operator a lot easier with an intuitive and simple WYSIWYG interface. It also offers the possibility to set-up multiple profiles with different access rights facilitating efficient maintenance while also eliminating risks of data leaks.

Closed-loop security

LED displays are used in various data-critical applications: government monitoring centers, military command posts, internal company presentations... Instead of using the standard transfer protocol, our Infinipix® processors work with a proprietary Barco engineered protocol to encrypt the sensitive data. Keep your crucial data from falling into the wrong hands, and trust the Infinipix® processing.

Fit-for-purpose

The NM100 can be configured with a fit-for-purpose licensing model, meaning you can expand and upgrade the system when you need additional advanced features.

Product specificaties

INFINIPIX® MANAGER NM100

General specifications

Afstandsbediening	<ul style="list-style-type: none">1x Ethernet: RJ-45 connector, running 1GbE connected to a control PC/ client network1x Ethernet: RJ-45 connector, running 1GbE used as control protocol link to an Infinipix™ Manager (NM100) for centralized management of multi-device Infinipix™ Processors (NP100) and one or more Displays.
Afmetingen (B x D x H)	216 x 286 x 70 mm (8.5 x 11.25 x 2.75 in)
Gewicht	2.72 kg (6 lbs)
Behuizing	metal
Software	MS Windows embedded operating system, running Infinipix™ Management Software
Aparte behuizing	rack shelf for side-by-side Infinipix™ Manager (NM100) and Infinipix™ Processor (NP100) <ul style="list-style-type: none">Width: 19" rackHeight: 2RUType: Metal
Omgevingstemperatuur	Operational: 0-40° Celsius (32-104° F)
Omgevingsvochtigheid	Operational: 10-85%, non-condensing
Type voeding	100-240VAC, 1.5A -50-60Hz
Energieverbruik	60 Watt
Standaarden	FCC: Part 15, Subpart B Section 15.107 & 15.109, Class A; CE: CISPR 24/ EN 55024, CISPR 22/ EN 55022 Level A, EN 61000-3-2 with A1, A2 2006 (only if 75W or above), IEC/EN/UL 60950-1, c-UL CSA C22.2 60950-1; ICES-003 Class A v4
Certificeringen	CE, ETL, RoHS, China RoHS, WEEE
Garantie	Full three-year parts and labor warranty

Laatst bijgewerkt: 30 May 2024

© 2024 Barco nv. Alle rechten voorbehouden. Gehele of gedeeltelijke reproductie zonder schriftelijke toestemming is verboden. Alle merknamen en productnamen zijn handelsmerken, geregistreerde handelsmerken of handelsnamen van hun respectieve houders. Als gevolg van voortdurende innovatie kunnen informatie en technische specificaties zonder voorafgaande kennisgeving worden gewijzigd. Controleer www.barco.com voor de nieuwste specificaties.