

# iQ Pro G400



## 技术规格

## IQ PRO G400

### 一般规格

光输出	4,200 ANSI lumen
亮度均匀性	>95 % for the total screen
对比度	>400 : 1 (full white/full black)
液晶面板	3 active matrix 1.3" diagonal XGA polysilicon LCD panels with Micro Lens Arrays and a resolution of 1024 x 768 pixels (aspect ratio 4:3).
分辨率	1024 x 768 (native)
网络	iQ Pro Server Specifications: -Processing Power: Pentium III socket with 1,2 Gigahertz Tualatin Celeron processor -Memory: 256 MB RAM -Storage: 40 GB hard disk -Video memory up to 64 MB -Inputs and outputs <ul style="list-style-type: none"><li>▪ PCMCIA slot for Wireless LAN cards, memory cards, Bluetooth, input extensions ...</li><li>▪ RJ45connector for Ethernet (10Mb/s) and Fast Ethernet (100Mb/s)</li><li>▪ 4 USB connectors</li><li>▪ Audio: 3,5 mm jacks for Microphone in, Line in and Line out</li></ul>

### 特性

- Advanced picture-in-picture - Seamless switching with effects - Standard cable basket - Standard light shutter - Advanced digital zoom

### 兼容性

The iQ Pro G400 is compatible with:

- All current video sources (PAL, SECAM, NTSC) in Composite, S-VHS, Component or RGB formats
- All currently proposed HDTV, extended and improved television standards (1080i, 720p)
- All computer graphics formats from VGA, SVGA, XGA, SXGA to UXGA
- Most Macintosh computers
- Electronic workstations with a resolution up to 1600 x 1200 pixels at 75 Hz
- Most computer sources with a pixel clock up to 160 MHz
- DVI sources up to SXGA

### 屏幕尺寸

From 1-6 m/3-20 ft.

### 输入

1x Configurable 5-Wire (BNC) for:  
Composite Video, S-Video, Component Video, RGBHV, RGBS, RGsB.  
1x Composite Video (BNC) (up to 7 Composite Video's when using all connectors on top input board)  
1x S-Video (4-pin mini-DIN) (up to 3 S-Video's when combining BNC's)  
1x VGA (D15 connector)  
1x DVI (Digital Visual Interface)

### 灯泡

2x 250 Watt UHP lamp, in lamp housing  
Typical lifetime: 1000 h/lamp.  
1000 hours in Dual Lamp Mode or max. 2000 hours/set in Single Lamp Mode.

### 镜头

Fixed focal length lenses are available with a throw ratio of 0.85:1 (very short throw ratio, specially designed for rear screen on-axis projection) or 7.0:1 (long throw).

Variable focus lenses with a throw distance of 1.3-1.8, 1.9-2.6, 3.0-6.0 times the screen width

### 扫描频率

Horizontal 15 kHz -110 kHz  
Vertical 25 Hz -150 Hz

### 镜头移动

QVD Lenses  
Motorized V shift: -30% +120%

For specific details per lens type: see lens product pages

### 尺寸(宽x长x高)

Projector body with cable basket: 415 mm (Max W) x 195 mm (Max H) x 565 mm (Max D)  
Projector body without cable basket: 415 mm (Max W) x 195 mm (Max H) x 487 mm (Max D)

### 净重

Net weight, body only: 12.9kg/28.5 lbs.

### 通信

1x D9 connectors for RS232 In/Out  
1x spherical IR receiver

### 噪音级别

### 电源

Power factor pre-regulated SMPS,  
90-254 VAC / 50-60Hz

### 功率消耗

Max 650 Watt

### 功率消耗

Max 2219 BTU/h

### 无缝切换

Standard

## 生成于: 09 Jul 2024

© 2024 巴可公司。保留所有权利。未经书面许可，禁止全部或部分复制。所有品牌名称和产品名称均为其各自持有者的商标、注册商标或商号。由于不断创新，信息和技术规格如有变更，恕不另行通知。请查看[www.barco.com.cn](http://www.barco.com.cn)以了解最新规格。