

CLM-HD6

6,000 lumens, 1080p HD, single-chip DLP projector



Barco's CLM-HD6 projector is designed on an efficient hardware platform. It offers a 6,000 lumens light output, full HD resolution and advanced input options at a highly competitive price. It is primarily designed for meeting rooms, medium-sized auditoriums, lobbies and museums.

Improved colors

The CLM-HD6 is a single-chip DLP projector with advanced color saturation and a full HD resolution. The projector's resolution and 6,000 lumens light output are ideal for single-screen applications that require a clear image and need to feature modern, high-definition images and video without quality loss.

Bright, silent and reliable

The CLM-HD6 is an attractive option for customers that want to project in bright HD and need the best quality guarantee at the most comfortable price. Due to its power-saving options, redundant lamp system and durable, proven technology, the CLM also offers a low total cost of ownership. If you want a reliable, bright and silent unit that does the job, the CLM-HD6 was designed for you.

Product specifications**CLM-HD6**

General specifications	
Projector type	Full HD single-chip DLP projector
Technology	0.65" DMD™ x1 color wheel: RGBYW
Resolution	1,920 x 1,080
Brightness	6,000 center lumens / 5,700 ANSI lumens
Contrast ratio	>1,300:1
Brightness uniformity	95%
Aspect ratio	16:9
ScenergiX	N/A
Lens type	CWH
Lens range	0.81:1 ; 1.27-1.52 ; 1.52-2.03 ; 2.03-3.85 ; 3.85-7.32
Optical lens shift	Vertical: -20% +120% / Horizontal: 20% (L) to 20% (R) on zoom lenses
Color correction	P7
Lamps	2x330W
Lamp lifetime (typical)	1,500 hrs / 2,000 hrs (max)
Transport with lamp	Yes
Lamp house, quick replace	Yes, auto lamp select
Customer bulb replace	N/A
Lamp warranty	120 days or 500 hrs
Sealed DLP™ core	Yes
Optical dowser	N/A
Advance Picture in Picture	Up to two sources simultaneously
Orientation	table -ceiling -vertical -side (portrait)
DMX 512	N/A
WARP	H+V keystone, pincushion
Integrated web server	N/A
CLO (constant light output)	Optional
3D	N/A

Product specifications**CLM-HD6**

Inputs	2 x HDMI (HDCP 1,3); 5-BNC (RGBHV, RGBS/RGBsB;YUV); VGA (RGBHV, RGBS/RGBsB;YUV); cinch (RGBs, YUV) Composite video; S-Video
Optional Inputs	N/A
Input resolutions	From NTSC up to UXGA (1600 x 1200), incl. HDTV (1920 X 1080)
Max. pixel clock	165 MHz
Software tools	Projection Toolset
Control	IR, RS232, 12v out
Network connection	10/100 Base-T, RJ-45 connection
Power requirements	100 -240V / 50 -60 Hz
Power consumption	905W / Standby mode:
Noise level (typical at 25°C/77°F)	40dB(A)
Operational ambient temperature	0°-40°C/ 32°-104°F
Operating humidity	0-80% (non-condensing)
Dissipation BTU	max. 3,087 BTU/h
Dimensions (WxLxH)	436 x 550 x 236mm / 17.16 x 21.65 x 9.29 inch
Weight	24kg (53 lbs)
Shipping Dimensions	(WxLxH) 661 x 822 x 380mm / 26.02 x 32.36 x 14.96 inch
Standard accessories	Power cord; wireless remote control, HDMI to DVI adaptor
Shipping Weight from Factory	27kg (59.5lbs)
Certifications	Complies with FCC rules & regulations, part 15 Class A and CE EN55022 Class A, RHoS
Warranty	3 years standard, 4th or 5th year optional

Last updated: 15 Mar 2023

© 2018 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.