

FLM HD18

Ultra silent, compact 18k lumens HD projector



Product specifications**FLM HD18**

General specifications	
Light output	18,000 center lumens 16,000 ANSI lumens
Resolution	HD 1080 (1920x1080px)
Brightness uniformity	> 90 % for the total screen
Contrast ratio	1800 : 1 (full field) high contrast mode: 2400 : 1 (full field)
Display	3-chip DLP HD (1920 x 1080 pixels, aspect ratio 16:9)
Convergence	Max allowed convergence drift is 0.5 pixel. This is checked on vertical and horizontal midlines only. Corners are not applicable for convergence error. This is measure with TLD 1.2 lens on axis.
Features	<ul style="list-style-type: none">■ Picture-in-picture■ Seamless switching with effects■ Standard light shutter■ Rigging points■ Carrying handle■ High contrast mode■ P7 color processing■ internal warp module
Picture-in-picture	2 sources simultaneously
Inputs	<ul style="list-style-type: none">■ configurable 5 cable (BNC)■ DVI■ (HD)SDI (+ loop through)■ DVI - HDCP
Outputs	HDSDI/ SDI loop out
Communication	<ul style="list-style-type: none">■ 1x RS-232C IN (D-9 connector)■ 1x RS-232C OUT (D-9 connector)■ 1x RS-232C IN (XLR connector)■ 2x prop. protocol (RJ45 connector)■ xlr and mini-jack for wired remote control
Compatibility	<ul style="list-style-type: none">■ All current video sources (PAL, SECAM, NTSC) in Composite, S-Video, Component or RGB formats■ All current HDTV sources■ All computer graphics formats from VGA, SVGA, XGA, SXGA, full HD, UXGA to QXGA■ Most Macintosh computers■ Electronic workstations with a resolution up to QXGA (2048 x 1536 pixels @ 60 Hz)■ Most computer sources with a pixel clock up to 300 MHz■ DVI sources up to DC2K (2048 x 1080)
Input source compatibility	max. input: up to QXGA (2048 x 1536)
Screen size	From 1 -12m / 3 -39ft. recommended
Scan Frequencies	pixel clock >162Mhz (up to QXGA @ 60Hz)
Network connection	10/100 base-T
On board display server	Ethernet control standard remote control projector over ethernet via Projector Toolset
Ambient temperature	Max 40°C (104°F)
Lamp	3.1 kW Xenon Warranty universal lamphouse: 750 Hrs

Product specifications**FLM HD18**

Lens Shift	Vertical: -10% to +110% Horizontal: -30% to +30% (small differences exist per lens type, e.g. short throw lenses have less shift)
Lens encoders	On zoom and focus (with TLD lenses)
ScenergiX	Standard horizontal & vertical electronic edge blending
Dust filters	Dense, high quality microfilters, also available as spare kit
Noise Level	58 dBA (at 40°C)
Mains Voltage	200 -240 V
Power consumption	3500 W (with universal lamp)
Power Dissipation	max 13,300BTU/h
Weight	99 kg (220 lbs)
Dimensions	WxLxH: 707 x 1025 x 548 mm (27.8 x 40.3 x 21.5 inch) incl. carrying handle + rigging points
Shipping Dimensions	Width: 92 cm Height: 95 cm Depth: 123 cm Floor Space: 1,1316 m ² Volume: 1,075020 m ³ Gross Weight: 161 kg
Safety Regulations	Compliant with UL1950 and EN60950
Electromagnetic Interference	complies with FCC rules & regulations, part 15 Class A and CE EN55022 Class A
Order Information	Projector: R9004450 Spare lamp: R9854535 6-pack dust filters: R9454470 24-pack dust filters: R9454480 RGB HV module: R9854440 FLM/SLM adaptor plate: R9854490 FLM carry handle: R9854530 FLM flight case: R9854510

Last updated: 15 Mar 2023

© 2018 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.