UDM-W22

21,000 lumens, WUXGA, 3-chip DLP large venue projector





- Lightest 22K laser projector in the market
- High residual value thanks to rugged design
- Remote fleet management and connectivity with Barco Insights Management Suite
- Unified Pulse electronics with Single Step Processing

Weighing less than 50kgs, this is the lightest 22K projector in the market. And while the compact and light-weight design of the UDM-W22 saves you lots of installation time and reduces shipping and labor costs, it never compromises on the quality or brightness of your projection. The UDM-W22 features WUXGA resolution and 21,000 lumens light output to deliver impactful experiences with mind-blowing colors. The UDM projector offers the widest color spectrum for 22K laser phosphor projection on the market outperforming the Rec. 709 color space.

Operational efficiency

Lift your creativity to unprecedented levels with the widest lens shift on the market and an extensive list of other peripherals which will facilitate a smooth installation and integration of the projector in your setup. Barco's unique FLEX2 feature allows you to tune and lock the brightness level or resolution for a specific show. The modular design supports fast maintenance and easy serviceability in the field.

Pulse Electronics

With the Barco Pulse proprietary Single Step Processing technology warping, scaling and 4K UHD processing is done in only one step. The result? Razorsharp images, market leading lowest latency, and less dark time than comparable solutions.

Connectivity

The Barco Insights Management Suite dashboard and remote log file access enables faster and more effective troubleshooting. Manage the brightness settings of your projector fleet and keep track of operating conditions



UDM-W22 Barco



anywhere and anytime through a secured cloud-based platform and integrated $3\mathsf{G}$ connectivity.

Long lifetime

Thanks to its robustness and the smart material choices, you can trust UDM to withstand the endurances of life on the road. With the laser phosphor light source, lamp-related costs and maintenance as well as image flicker, belong to the past. Barco's outstanding integrated laser cooling prevents overheating and the Constant Light Output functionality guarantees constant brightness and color across the projector's lifetime.

| Product specifications | UDM-W22 |
|-----------------------------|---|
| General specifications | |
| Projector type | WUXGA 3-chip DLP digital projector |
| Technology | 0.96" DMD TM x3 |
| Resolution | 1,920 x 1,200 |
| Brightness | 21,000 center lumens / 20,000 ansi lumens / 22,000 ISO lumens* |
| Contrast ratio | Full field 2200:1 / Barco Dyna Black 20000:1 |
| Optical lens shift | Vertical between -100% to +130%, depending on lens |
| | Horizontal up to +/-40%, depending on lens |
| | Motorized zoom and focus (with lens memory on TLD lenses) |
| | Motorized lens shift (with position memory on all lenses) |
| | Motorized terms smilt (with position memory on all terises) |
| Light source | Laser B + Red compensator and inorganic Ph wheel |
| Brightness uniformity | 93% |
| Light source lifetime | 20,000hr (at 100% laser power, DynaBlack = off) |
| Color correction | P7 |
| Optical dowser | Digital + mechanical internal |
| Aspect ratio | 16:10 |
| Lenses | TLD+ 0,37; 0,65-0,85; 0.73:1; 1.2:1; 0,8-1,16; 1,25-1.6:1; 1.5-2.0:1; 2.0-2.8:1; 2.8-4.5:1; 4.5-7.5:1; 7.5-11.5:1 |
| Orientation | 360° |
| Sealed DLP™ core | Standard |
| Inputs | Single HDBaseT; HDMI2.0 (HDCP2.2, HDR10); DP1.2 (HDCP 1.3); Quad 3G/12G SDI/BarcoLink ULTRA |
| Input resolutions | From NTSC up to 4K (4,096 x 2,160) |
| | Refresh rates: |
| | 24hz to 120 Hz 4K/4KUHD (4096 x 2160 / 3860 x 2400) to 240hz WQXGA (2560 x 1600) |
| Processing | Pulse electronics |
| Picture-by-picture | Two sources simultaneously |
| CLO (constant light output) | Standard |
| DMX 512 | Standard |
| WARP | Direct adjust OSD + toolset |
| ScenergiX | Horizontal and vertical edge blending |
| Image processing | Embedded warp & blend |
| Keystone correction | Yes |
| Integrated web server | Yes |
| Software tools | Projector Toolset + Android** app + iOS** app + Insights Management Suite (IMS) |
| Control | XLR wired + IR, RS232, Wifi**, GSM ** |
| 3D | Active eye wear (optional), passive circular (optional); 2 flash up to 200Hz |
| Optional Inputs | Quad DP1.2 / Fiber SFP |
| Max. pixel clock | 600 MHz |
| Network connection | 10/100 base-T, RJ-45 connection, Wifi** |

| Product specifications | UDM-W22 |
|------------------------------------|---|
| Dimensions (WxLxH) | 725 x 540 x 339 mm / 28.54 x 21.25 x 13.36 inches |
| Weight | 48 kg (105 lbs) / shipping weight from factory: 61 kg (134 lbs) |
| Power requirements | 120-160 V (max 70% brightness)18.5A / 200-240V (+/-10%), 13.5A, 50-60Hz |
| Operational humidity | 0-80% (non condens) |
| Max. power consumption | 1800W nom/ 2200w max @ 230 volts ECO STBY 1300W nom/ 1530w max @ 120 volts ECO STBY |
| Noise level (typical at 25°C/77°F) | 48 dB(A) |
| Operational ambient temperature | 0-40°C / 32°-104°F *** |
| Notes | *Brightness levels +/-10% |
| | ** Wifi and GSM options are not available in all countries. Check with your Barco representative for more info. |
| | ***at higher altitude light output might be dimmed |
| Dissipation BTU | Max. 6,890 BTU/h |
| Shipping Dimensions | incl. pallet |
| | (WxLxH) 850 x 665 x 613 mm / 33.46 x 26.18 x 24.13 inches |
| Standard accessories | Power cord, wireless / XLR wired rugged remote control |
| Certifications | Compliant with UL60950-1 and EN60950-1, complies with FCC rules & regulations, part 15 Class A and CE EN55032 Class A, Rohs |
| Warranty | 3 years |
| | |

Last updated: 09 Apr 2024

© 2018 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.

