

WSG-110

Small form factor thin client for SecureStream



Barco's WSG-110 thin client is a small form factor to display encoded streams coming from an IP network. It supports standard H.264, Barco's low-latency Video2Data (V2D), Barco ProServer/Virtual Network Computing (VNC) and Remote Display Protocol (RDP) decoding.

Low noise thin client for up to two displays

The WSG-110 is designed and fully qualified for Barco's SecureStream solution. Once connected to a SecureStream system, the pre-configured appliance enables customers to capture networked source information from anywhere. It displays these sources with a user-friendly user interface.

Multiple appliances can be combined to show sources as part of a composed desktop on monitors of an OpSpace workstation, a truly unified workspace for mission-critical applications.

This thin client can process up to eight HD-quality sources and allows organizing visual and interactive content as a smart multi-viewer to enhance knowledge and improve decision-making.

Features

- Pre-configured thin client for SecureStream
- Linux based operating system
- Intel® i7 Quad Core™ processor for low-latency application processing and software based media decoding
- Processes up to eight HD sources
- Universal IP streaming video decoding (H.264, V2D, ProServer/VNC, RDP)
- Silent operation
- Small form factor
- Flexible mounting options

Spécifications techniques

WSG-110

Spécifications générales

Plateformes	SecureStream
Processeur	Intel(R) Core(TM) i7 Quad core CPU 3.4GHz
Mémoire	8 GB RAM
Disque dur	128 GB SSD
Réseau	2x 1Gb/s LAN
Carte graphique	Intel HD Graphics 630
Sorties	Up to 2x displays HD 1920x1200 @60Hz via DisplayPort (HDMI via included adapters)
Entrée	IP video sources (H.264), Video2Data (Barco V2D), Virtual Network Computing (VNC), Remote Desktop Protocol (RDP)
Version	60 x 190 x 190 mm 2.36 x 7.48 x 7.48 in Packed: 230 x 260 x 308 mm 9.06 x 10.24 x 12.13 in
Poids	2.2kg Packed: 4.5kg
Alimentation	External PSU 150W / 90 – 264 VAC / 47 – 63 Hz
Consommation électrique	Typ. 83W max. 110W
Plage de température	0° -40° C 32° -104° F
Humidité	Max. 80% (non-condensing)
MTBF	47,500 h
Niveau sonore	Max. 32dbA (measured at 1m/32.8ft distance at 22°C/72°F)
Conformité	CE, CB, UL, RCM, BIS, CU-EAC, FCC Class A CCC contact Barco Sales
Montage	Order no. R9811098 P110 VESA Mount (for 1x OPS-110 + 1x PSU) R9811099 P110 Rack Mount (for 2x OPS-110 + 2x PSU)

Créé le : 09 Jul 2024

© 2024 Barco nv. Tous droits réservés. La reproduction partielle ou intégrale sans autorisation écrite préalable est interdite. Les noms de marques ou de produits sont des marques commerciales, des marques déposées ou des appellations commerciales appartenant à leurs détenteurs respectifs. Pour des raisons d'innovation continue, les informations et les caractéristiques techniques sont susceptibles d'être modifiées sans préavis. Veuillez consulter www.barco.com pour les dernières spécifications.