RLM G5i Performer

With its compact design and sealed optics, the RLM G5i Performer is an ideal all-round projector suitable to both the rental as well as staging markets.





Product specifications	RLM G5I PERFORMER
General specifications	
Light output	4500 ANSI Lumen
Resolution	1024 x 768 (native)
Contrast ratio	1000 : 1 (full field)
High contrast mode	Available with special lenses
Brightness uniformity	> 90%
Lamp	2 x 250 W mercury
	max. lifetime: 1500 hrs typ. lifetime: 1000 hrs min. lifetime: 750 hrs
Noise level (@ 20°C -68°F)	42 dBa
Noise level (@ 40°C -104°F)	46,5 dBa
Ambient temperature	Max 40°C (104°F)
Power consumption	700 W
Mains Voltage	92-240 V
Weight	Projector: 25 kg (56 lbs) Frame: 5 kg (11 lbs)
Dimensions (WxLxH)	705 x 707,8 x 316,5 mm
Light shutter	Standard
Sealed DLP™ core	Standard
ScenergiX	Standard horizontal and vertical electronic edge blending
Seamless Switching	Standard (wipes, fades,)
Picture-in-picture	Up to 4 sources simultaneously (2 data, 1 video and 1 SDI)
Digital zoom	Standard
Lens encoders	On zoom and focus (with TLD lenses)
Linked Constant Light Output	not available
Input source compatibility	1600 x 1200 (max. input)
Fixed Inputs	 1x configurable 5 cable (BNC) 1x composite Video (BNC) 1x S-Video (4-pin DIN) 1x analogue RGB (D15 Connector) 1x SDI (+ loop through) 1x DVI (Digital Visual Interface)
Modular inputs	not available
Control	 1 x RS-232 / 422 IN 1 x XLR female (2 way) build-in RF remote transceiver (optional)
Order Information	Projector Body: R9010320 Spare Dual Lamp:R9852940

Last updated: 09 Jul 2024

© 2024 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.

BARCO