

# iq G210L



## 技术规格

## IQ G210L

### 一般规格

光输出	2,200 ANSI lumen
亮度均匀性	Brightness uniformity: >95 % for the total screen
分辨率	1024 x 768 (native)
液晶面板	3 active matrix 1.4" diagonal XGA polysilicon LCD panels with Micro Lens Arrays and a resolution of 1024 x 768 pixels (aspect ratio 4:3). LCD panels are selected for a minimum of pixel defects.
灯泡	2x 120 Watt UHP lamp, in lamp housing, pre-aligned for max. light output. Typical lifetime: 6000 h/lamp. 6000 hours in Dual Lamp Mode or max. 12000 hours/set in Single Lamp Mode.
镜头	Fixed focal length lenses are available with a throw ratio of 0.85:1 (very short throw ratio, specially designed for rear screen on-axis projection) or 7.0:1 (long throw).  Variable focus lenses with a throw distance of 1.3-1.8,1.9-2.6,3.0-6.0 times the screen width
屏幕尺寸	From 1-6m/3-20ft.
对比度	>800:1 (full white/full black)
扫描频率	Horizontal 15kHz -110kHz Vertical 25 Hz -150 Hz
特性	<ul style="list-style-type: none"><li>· Advanced picture-in-picture</li><li>· Seamless switching with effects</li><li>· Standard cable basket</li><li>· Standard light shutter</li><li>· Advanced digital zoom</li></ul>
兼容性	The iQ G210L is compatible with: <ul style="list-style-type: none"><li>· All current video sources (PAL,SECAM, NTSC) in Composite, S-VHS, Component or RGB formats</li><li>· All currently proposed HDTV, extended and improved television standards (1080i, 720p)</li><li>· All computer graphics formats from VGA, SVGA, XGA, SXGA to UXGA</li><li>· Most Macintosh computers</li><li>· Electronic workstations with a resolution up to 1600 x 1200 pixels at 75 Hz</li><li>· Most computer sources with a pixel clock up to 160 MHz</li><li>· DVI sources up to SXGA</li></ul>
输入	1x Configurable 5-Wire (BNC) for: Composite Video, S-Video, Component Video, RGBHV, RGBS, RGB. 1x Composite Video (BNC) (up to 7 Composite Video's when using all connectors on top input board) 1x S-Video (4-pin mini-DIN) (up to 3 S-Video's when combining BNC's) 1x VGA (D15 connector) 1x DVI (Digital Visual Interface)
尺寸(宽x长x高)	Projector body with cable basket: 415 mm (Max W) x 195 mm (Max H) x 565 mm (Max D) Projector body without cable basket: 415 mm (Max W) x 195 mm (Max H) x 487 mm (Max D)
通信	1x D9 connectors for RS232 In/Out 1x spherical IR receiver
噪音级别	
电源	Power factor pre-regulated SMPS, 90-254 VAC / 50-60Hz
功率消耗	Max 350 Watt
功率消耗	Max 1195 BTU/h
安全级别	Compliant with UL1950 and EN60950
电磁干扰	Barco's iQ G210L complies with FCC rules & regulations, part 15 Class B and CE EN55022 Class B
净重	Net weight: Body only 12.9 kg / 28.5 lbs. Shipping weight: <ul style="list-style-type: none"><li>· without lens max.17.5 kg / 38.5 lbs.</li><li>· with lens: max.20 kg / 44 lbs</li></ul>
镜头移动	QVD Lenses Motorized V shift: -30% +110%  For specific details per lens type: see lens product pages
无缝切换	Standard
网络连接	Refer to iQ Pro G210L

生成于: 09 Jul 2024

© 2024 巴可公司。保留所有权利。未经书面许可, 禁止全部或部分复制。所有品牌名称和产品名称均为其各自持有者的商标、注册商标或商号。由于不断创新, 信息和技术规格如有变更, 恕不另行通知。请查看[www.barco.com.cn](http://www.barco.com.cn)以了解最新规格。