

Nio Color 8MP (MDNC-8132)

Your perfect fit for radiology diagnostic reading and clinical collaboration at home, in the hospital, anywhere



- Large 32" display
- 8MP screen resolution
- Integrated multimedia functionalities
- One display for multiple workstations
- Automated, remote QA and compliance

Barco's Nio Color 8MP display is the ideal choice for radiology image interpretation in various settings. It seamlessly merges our acclaimed image quality and detail with built-in features that make collaboration with peers – from any location – easy and clutter-free.

Excellent 8MP image quality on a large 32" screen

Whether you're working in an office, at home, or any other location, a solid setup is crucial. With its remarkable 8MP resolution and generous 32" screen, Nio Color 8MP empowers you to combine the information and images you need on a single screen.

The monitor includes our Intuitive Workflow Tools and cutting-edge technologies:

- SteadyGray for precise and consistent representation of grays
- SteadyColor for accurate and consistent representation of colors
- I-Guard for stable performance across the display's full lifetime
- Uniform Luminance Technology for screen-wide uniformity correction
- Ambient Light Compensation for optimal viewing in various lighting conditions
- RapidFrame for sharp and fast image rendering when scrolling through cine images

Your perfect fit for reading radiology images, anywhere

In addition to the Nio Color 8MP's exceptional core features, you also get:

- Integrated camera, speaker, and microphone



- Our advanced screensharing tool Multi-Display Confer, for smooth virtual collaboration
- KVM functionality for effortless switching between multiple workstations
- Daisy chaining to keep your desk free of cable clutter

Stable performance, remotely managed

Enjoy automated QA and compliance for a stable performance anywhere, during the full lifetime of your monitor, thanks to QAWeb Enterprise. Finally, Barco's all-inclusive warranty assures you a full return on investment over at least 5 to 7 years of your display.

A+ ecolabel for Nio Color 8MP

The Nio Color 8MP has been subjected to Barco's ecoscoring protocol and has received an A+ rating. Some key factors that contributed to this rating are:

- Automatic standby mode when device is not in use
- Use of plastics containing 35% post-consumer recycled content
- >50% halogen-free cables & >65% halogen-free PCBs
- >90% recyclable packaging
- 5 years all-inclusive warranty, extendable to 7 years

Product specifications**NIO COLOR 8MP (MDNC-8132)****General specifications**

| | |
|---------------------------------------|--|
| Screen technology | IPS |
| Active screen size (diagonal) | 812.80 mm (32.0") |
| Active screen size (H x V) | 708.48 x 398.52 mm (27.9 x 15.7") |
| Aspect ratio (H:V) | 16:9 |
| Resolution | 8MP (3840 x 2160 pixels @ 60 Hz) |
| Pixel pitch | 0.1845 mm |
| Color imaging | Yes |
| Gray imaging | Yes |
| Bit depth | 30 Bit |
| Viewing angle (H, V) | 178° |
| Uniformity correction | ULT |
| SteadyGray | Yes |
| SteadyColor | Yes (in MXRT Display Controller), when used as a system with MXRT Display Controller & QAWeb Enterprise |
| Pathology Setting | Yes |
| Color gamut NTSC | 94% |
| Color gamut sRGB | 132% |
| sRGB Delta E2000 (typical) | Average: < 3 Max: < 5 |
| RapidFrame | Yes |
| Ambient light presets | Yes, reading room selection |
| Ambient light sensor | Yes |
| Front sensor | Yes, I-Guard |
| Presence sensor | Yes |
| Maximum luminance (panel typical) | 850 cd/m ² |
| DICOM calibrated luminance | 420 cd/m ² |
| Contrast ratio (panel typical) | 1350:1 |
| Response time ((Tr + Tf)/2) (typical) | 12.7 ms |
| Housing color | Black (RAL 9004) / White (RAL 9003) |
| Video input signals | 2x DisplayPort 1.4 |
| Video output signals | 1x DisplayPort (MST) |
| USB ports | 2x USB-B 2.0 upstream (endpoint) 5x USB-A 2.0 downstream (of which 1 charge port) |
| KVM switch | Yes |
| Power rating | 24 Vdc, 8.3 A |
| Power requirements | This device shall only be powered by the medical approved power supply of Adapter Tech., type ATM200T-P240 Input: 100-240 Vac, 50-60 Hz, 2.5-0.9 A Output: 24 Vdc, 8.3 A |
| Power consumption | 60 W (nominal) < 0.35 W (switched off) |
| Dimensions with stand (W x H x D) | 743 x 518~618 x 238 mm |
| Dimensions w/o stand (W x H x D) | 743 x 459 x 63 mm |
| Dimensions packaged (W x H x D) | 898 x 752 x 358 mm |
| Net weight with stand | 13 kg |
| Net weight w/o stand | 8.4 kg |
| Net weight packaged | 21 kg (without optional accessories) |
| Tilt | -5° to +25° |
| Swivel | -30° to +30° |
| Pivot | N/A |
| Height adjustment range | 100 mm |
| Mounting standard | VESA (100 mm) |
| Screen protection | N/A |
| Recommended modalities | All digital images, except digital mammography. |

Product specifications

NIO COLOR 8MP (MDNC-8132)

| | |
|------------------------------|--|
| Certifications | CE0123 (Medical Device) FDA 510(k) K233693 CCC(China), KC (Korea), INMETRO (Brazil), BIS (India), EAC (Russia) (Pending) Safety specific: IEC 60950-1:2005 + A1:2009 + A2:2013 EN60950-1:2006 + A1:2010 + A11:2009 + A12:2011 + A2:2013 IEC 62368-1:2018 EN IEC 62368-1:2020 + A11:2020 IEC60601-1:2005 + A1:2012 + A2:2020 EN 60601-1:2006 + A1:2013 + A12:2014 + A2:2021 AAMI ES 60601-1:2005 + A1:2012 + A2:2021 CAN/CSA C22.2 No. 60601-1:2014 (Reaffirmed 2022) EMI specific: IEC 60601-1-2:2014+A1:2020 (ed4.1) EN 60601-1-2:2015 + A1:2021 (ed4.1) FCC part 15 Class B ICES-001 Level B VCCI (Japan) (Pending) Environmental: EU RoHS, China RoHS, REACH, Canada Health, WEEE, Packaging Directive |
| Supplied accessories | User Guide Quick Install Sheet Documentation disc System sheet Video cables Mains cables USB cable External power supply |
| Optional accessories | Display controller Touch pad |
| QA software | QAWeb Enterprise |
| Warranty | 5 years, including 20000 hours backlight warranty |
| Operating temperature | 0 °C to 35 °C (20 °C to 30 °C within specs) |
| Storage temperature | -20 °C to +60 °C |
| Operating humidity | 8 % to 70 % (non-condensing) |
| Storage humidity | 5 % to 70 % (non-condensing) |
| Operating pressure | 70 kPa |
| Storage pressure | 50 to 106 kPa |

Last updated: 26 Jun 2025

© 2025 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.