

iQ G400



Especificações técnicas

IQ G400

Especificações gerais

Saída de luz	4,200 ANSI lumen
Uniformidade de brilho	Brightness uniformity: >95 % for the total screen
Telas de LCD	3 active matrix 1.3" diagonal XGA polysilicon LCD panels with Micro Lens Arrays and a resolution of 1024 x 768 pixels (aspect ratio 4:3). LCD panels are selected for a minimum of pixel defects.
Resolução	1024 x 768 (native)
Lâmpada	2x 250 Watt UHP lamp, in lamp housing, pre-aligned for max. light output. Typical lifetime: 1000 h/lamp. 1000 hours in Dual Lamp Mode or max. 2000 hours/set in Single Lamp Mode.
Lentes	Fixed focal length lenses are available with a throw ratio of 0.85:1 (very short throw ratio, specially designed for rear screen on-axis projection) or 7.0:1 (long throw). Variable focus lenses with a throw distance of 1.3-1.8,1.9-2.6,3.0-6.0 times the screen width
Tamanho da tela	From 1-6 m/3-20 ft.
Razão de contraste	>400 : 1 (full white/full black)
Frequências de Varredura	Horizontal 15 kHz -110 kHz Vertical 25 Hz -150 Hz
Recursos	<ul style="list-style-type: none">• Advanced picture-in-picture• Seamless switching with effects• Standard cable basket• Standard light shutter• Advanced digital zoom
Compatibilidade	The IQ G400 is compatible with: <ul style="list-style-type: none">• All current video sources (PAL,SECAM, NTSC) in Composite, S-VHS, Component or RGB formats• All currently proposed HDTV, extended and improved television standards (1080i, 720p)• All computer graphics formats from VGA, SVGA, XGA, SXGA to UXGA• Most Macintosh computers• Electronic workstations with a resolution up to 1600 x 1200 pixels at 75 Hz• Most computer sources with a pixel clock up to 160 MHz• DVI sources up to SXGA
Entradas	1x Configurable 5-Wire (BNC) for: Composite Video, S-Video, Component Video, RGBHV, RGBS, RGsB. 1x Composite Video (BNC) (up to 7 Composite Video's when using all connectors on top input board) 1x S-Video (4-pin mini-DIN) (up to 3 S-Video's when combining BNC's) 1x VGA (D15 connector) 1x DVI (Digital Visual Interface)
Dimensões (LxPxA)	Projector body with cable basket: 415 mm (Max W) x 195 mm (Max H) x 565 mm (Max D) Projector body without cable basket: 415 mm (Max W) x 195 mm (Max H) x 487 mm (Max D)
Comunicação	1x D9 connectors for RS232 In/Out 1x spherical IR receiver
Nível de Ruído	
Energia de CA	Power factor pre-regulated SMPS, 90-254 VAC / 50-60Hz
Consumo de energia	Max 620 Watt
Dissipação de Potência	Max 2117 BTU/h
Peso	Net weight: Body only 12.9 kg / 28.5 lbs. Shipping weight: <ul style="list-style-type: none">• without lens max.17.5 kg / 38.5 lbs.• with lens: max.20 kg / 44 lbs.
Deslocamento de Lente	QVD Lenses Motorized V shift: -30% +120% For specific details per lens type: see lens product pages
Comutação sem emendas	Standard
Conexão de rede	Refer to IQ Pro G400

Gerada em: 09 Jul 2024

© 2024 Barco nv. Todos os direitos reservados. A reprodução total ou parcial sem permissão por escrito é proibida. Todos os nomes de marca e produto são marcas comerciais, marcas comerciais registradas ou nomes dos respectivos proprietários. Por causa da inovação contínua, as informações e as especificações técnicas estão sujeitas a alterações sem aviso prévio. Verifique www.barco.com para obter as especificações mais recentes.