

iQ Pro R300



技术规格

IQ PRO R300

一般规格

光输出	3,300 ANSI lumen
亮度均匀性	>95 % for the total screen
对比度	>400: 1 (full white/full black)
液晶面板	3 active matrix 1.3" diagonal XGA polysilicon LCD panels with Micro Lens Arrays and a resolution of 1366 x 1024 pixels (aspect ratio 4:3).
分辨率	1366 x 1024 (native)
网络	iQ Pro Server Specifications: -Processing Power: Pentium III socket with 1,2 Gigahertz Tualatin Celeron processor -Memory: 256 MB RAM -Storage: 40 GB hard disk -Video memory up to 64 MB -Inputs and outputs

- PCMCIA slot for Wireless LAN cards, memory cards, Bluetooth, input extensions ...
- RJ45 connector for Ethernet (10Mb/s) and Fast Ethernet (100Mb/s)
- 4 USB connectors
- Audio: 3,5 mm jacks for Microphone in, Line in and Line out

特性

- Advanced picture-in-picture
- Seamless switching with effects
- Standard cable basket
- Standard light shutter
- Advanced digital zoom

兼容性

The iQ Pro R300 is compatible with:

- All current video sources (PAL, SECAM, NTSC) in Composite, S-VHS, Component or RGB formats
- All currently proposed HDTV, extended and improved television standards (1080i, 720p)
- All computer graphics formats from VGA, SVGA, XGA, SXGA to UXGA
- Most Macintosh computers
- Electronic workstations with a resolution up to 1600 x 1200 pixels at 75 Hz
- Most computer sources with a pixel clock up to 160 MHz DVI sources up to SXGA

屏幕尺寸

From 1-6 m/3-20 ft.

输入

1x Configurable 5-Wire (BNC) for:
Composite Video, S-Video, Component Video, RGBHV, RGBS, RGBsB.
1x Composite Video (BNC) (up to 7 Composite Video's when using all connectors on top input board)
1x S-Video (4-pin mini-DIN) (up to 3 S-Video's when combining BNC's)
1x VGA (D15 connector)
1x DVI (Digital Visual Interface)

灯泡

2x 200 Watt UHP lamp, in lamp housing
Typical lifetime: 1500 h/lamp.
1500 hours in Dual Lamp Mode or max. 3000 hours/set in Single Lamp Mode

镜头

Fixed focal length lenses are available with a throw ratio of
0.85:1 (very short throw ratio, specially designed for rear screen on-axis projection) or 7.0:1 (long throw).

Variable focus lenses with a throw distance of 1.3-1.8, 1.9-2.6,
3.0-6.0 times the screen width

扫描频率

Horizontal 15 kHz -110 kHz
Vertical 25 Hz -150 Hz

镜头移动

V shift: -30% +120%

尺寸(宽x长x高)

Projector body with cable basket: 415 mm (Max W) x 195 mm (Max H) x 565 mm
Projector body without cable basket: 415 mm (Max W) x 195 mm (Max H) x 487 mm (Max D)

净重

Net weight, body only: 12.9kg/28.5 lbs.

通信

1x D9 connectors for RS232 In/Out
1x spherical IR receiver

噪音级别

电源

Power factor pre-regulated SMPS,
90-254 VAC / 50-60Hz

功率消耗

Max 550 Watt

功率消耗

Max 1878 BTU/h

安全级别

Compliant with UL1950 and EN60950

电磁干扰

BARCO's iQ Pro R300 complies with FCC rules & regulations, part 15 Class B and CE EN55022 Class B

无缝切换

Standard

生成于: 09 Jul 2024

© 2024 巴可公司。保留所有权利。未经书面许可, 禁止全部或部分复制。所有品牌名称和产品名称均为其各自持有者的商标、注册商标或商号。由于不断创新, 信息和技术规格如有变更, 恕不另行通知。请查看www.barco.com.cn以了解最新规格。