ProScribe (MTPP-0212)

12-inch ruggedized wireless thin client





Product specifications	PROSCRIBE (MTPP-0212)
General specifications	
СРИ	Intel® Atom N270 (x86 compatible)
CPU Speed	1.6 GHz
RAM Size	1 GB DDR2 RAM
Flash Memory Size	4 GB
Operating system	MS Windows® Embedded standard
Technology	Transmissive TFT LCD
Touch screen	Resistive type
Active screen diagonal	307 mm (12.1")
Active screen width	245.8 mm (9.68")
Active screen height	184.3 mm (7.26°)
Color imaging	Yes
Gray imaging	No
Resolution	XGA (1024 x 768)
Luminance	170 cd/m² (typical)
Contrast	250:1 (typical)
Dimensions	313.5 x 235.5 x 35.2 mm (12.34 x 9.27 x 1.39")(W x H x D)
Weight	1,75 kg (3.85 lbs)
Approvals	ITE version: EN/IEC 60950-1, UL 60950-1 EMC: FCC CFR 47 P.15 Sub B -Class B, EN 55022 / CISPR 22 -Class B, EN 55024, C-UL-US, CE, FCC Medical version (optional) Safety: N/IEC 60601-1, UL 60601-1 EMC: IEC 60601-1-2, EN 55011 / CISPR 11 -Class B Marks: C-UL-US, CE, FCC All versions: Radio: FCC CFR 47 P.15 Sub C, RSS-210, SAR, IC ID, R
Operating temperature	0°C to +35°C (32 to 95°F)
Ambient Light Compensation (ALC)	No
Uniformity Technology	No

© 2024 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.

