

# iQ G400



## Specifiche tecniche

## IQ G400

### Specifiche generali

Emissione luminosa	4,200 ANSI lumen
Uniformità della luminosità	Brightness uniformity: >95 % for the total screen
Pannelli LCD	3 active matrix 1.3" diagonal XGA polysilicon LCD panels with Micro Lens Arrays and a resolution of 1024 x 768 pixels (aspect ratio 4:3). LCD panels are selected for a minimum of pixel defects.
Risoluzione	1024 x 768 (native)
Lampada	2x 250 Watt UHP lamp, in lamp housing, pre-aligned for max. light output. Typical lifetime: 1000 h/lamp. 1000 hours in Dual Lamp Mode or max. 2000 hours/set in Single Lamp Mode.
Ottiche	Fixed focal length lenses are available with a throw ratio of 0.85:1 (very short throw ratio, specially designed for rear screen on-axis projection) or 7.0:1 (long throw).  Variable focus lenses with a throw distance of 1.3-1.8,1.9-2.6,3.0-6.0 times the screen width
Dimensioni schermo	From 1-6 m/3-20 ft.
Rapporto di contrasto	>400 : 1 (full white/full black)
Frequenze di scansione	Horizontal 15 kHz -110 kHz Vertical 25 Hz -150 Hz
Caratteristiche	<ul style="list-style-type: none"><li>• Advanced picture-in-picture</li><li>• Seamless switching with effects</li><li>• Standard cable basket</li><li>• Standard light shutter</li><li>• Advanced digital zoom</li></ul>
Compatibilità	The IQ G400 is compatible with: <ul style="list-style-type: none"><li>• All current video sources (PAL,SECAM, NTSC) in Composite, S-VHS, Component or RGB formats</li><li>• All currently proposed HDTV, extended and improved television standards (1080i, 720p)</li><li>• All computer graphics formats from VGA, SVGA, XGA, SXGA to UXGA</li><li>• Most Macintosh computers</li><li>• Electronic workstations with a resolution up to 1600 x 1200 pixels at 75 Hz</li><li>• Most computer sources with a pixel clock up to 160 MHz</li><li>• DVI sources up to SXGA</li></ul>
Ingressi	1x Configurable 5-Wire (BNC) for: Composite Video, S-Video, Component Video, RGBHV, RGBS, RGSB. 1x Composite Video (BNC) (up to 7 Composite Video's when using all connectors on top input board) 1x S-Video (4-pin mini-DIN) (up to 3 S-Video's when combining BNC's) 1x VGA (D15 connector) 1x DVI (Digital Visual Interface)
Dimensioni (PXLXA)	Projector body with cable basket: 415 mm (Max W) x 195 mm (Max H) x 565 mm (Max D) Projector body without cable basket: 415 mm (Max W) x 195 mm (Max H) x 487 mm (Max D)
Comunicazione	1x D9 connectors for RS232 In/Out 1x spherical IR receiver
Livello di rumore	
Alimentazione CA	Power factor pre-regulated SMPS, 90-254 VAC / 50-60Hz
Consumo energetico	Max 620 Watt
Dissipazione alimentazione	Max 2117 BTU/h
Peso	Net weight: Body only 12.9 kg / 28.5 lbs. Shipping weight: <ul style="list-style-type: none"><li>• without lens max.17.5 kg / 38.5 lbs.</li><li>• with lens: max.20 kg / 44 lbs.</li></ul>
Spostamento obiettivo	QVD Lenses Motorized V shift: -30% +120%  For specific details per lens type: see lens product pages
Commutazione continua	Standard
Connessione in rete	Refer to IQ Pro G400

Generato il: 09 Jul 2024

© 2024 Barco nv. Tutti i diritti riservati. La riproduzione totale o parziale è proibita in assenza di autorizzazione scritta. Tutti i nomi di marchi e di prodotti sono marchi, marchi registrati o nomi commerciali dei rispettivi proprietari. A causa delle continue innovazioni, le informazioni e le specifiche tecniche sono soggette a modifiche senza preavviso. Controlla [www.barco.com](http://www.barco.com) per le specifiche più recenti.