

DP-1200

2K Digital cinema projector for screens up to 12m (40ft)



Product specifications**DP-1200****General specifications**

Digital MicroMirror Device™	3 x 0.98" DC2K dark metal devices
Native resolution	2048 x 1080
Housing	Hermetically sealed DMD™ and optical assembly
Lamp	1.2kW -2kW Xenon lamp size
Screen Width	Screen width (screen gain 1.2) @ 14ft* : up to 12m -40ft (*): = ± 10% variation possible between units
Contrast ratio	2000:1
Digital Video Inputs	2 x SMPTE 292M inputs 2 x DVI input both selectable as single or as dual link
Prime lenses	1.2-1.8 1.4-2.05 1.6-2.5 1.95-3.2 2.4-3.9
Projector diagnostics	via PC touch panel via Communicator control software via SNMP agent
Power requirements	200–240 VAC, 50–60 Hz, 15 amps at 200 VAC
Dimensions	projector: 505(H) x 689(W) x 1018(D) mm 19.9(H) x 27.1(W) x 40.0(D) inch NB: min. 5 cm of air inlet spacing required at the bottom of projector
Weight	projector: 93kg (205lbs)
Ambient temperature	max. 35°C / 95°F
Options	CLO-constant light output ACS-2048 SNMP agent
Mounting	universal pedestal (optional)

Last updated: 09 Jul 2024

© 2024 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.