BARCOData 708 + Iris^3

Specifiche tecniche	BARCODATA 708 + IRIS³
Specifiche generali	
Compatibilità	Horizontal autolock scan frequency of 15-69 kHz Vertical autolock scan frequency of 37-210 Hz Standard Video, S-Video and professional Component Video RGB signals from a wide range of PC graphics boards with resolutions up to 1280 by 1024 pixels/60 Hz Wideband 75 MHz RGB amplifiers A full complement of input signal connections
Contrasto	>1000:1 (full field contrast)
Emissione luminosa	1100 Lumen (at 10 % peak white) 130 ANSI Lumen (Economy mode) 170 ANSI Lumen (Normal mode) 200 ANSI Lumen (Boost mode)
Dimensioni schermo	Min.: 1.4 m x 1.05 m (4.6' x 3.5') Max.: 6 m x 4.5 m (20' x 15')

Generato il: 09 Jul 2024

© 2024 Barco nv. Tutti i diritti riservati. La riproduzione totale o parziale è proibita in assenza di autorizzazione scritta. Tutti i nomi di marchi e di prodotti sono marchi, marchi registrati o nomi commerciali dei rispettivi proprietari. A causa delle continue innovazioni, le informazioni e le specifiche tecniche sono soggette a modifiche senza preavviso. Controlla www.barco.com per le specifiche più recenti.