

HDMI 2.0 Quad input card



- Four HDMI™ 2.0 connectors
- Supports up to 4x 1600p60, or 2x 4K@60p/UHD per card (single cable)

Supports up to 4x 1600p60, or 2x 4K@60p/UHD per card (single cable)

- HDCP 2.2 compliant

HDCP 2.2 compliant

- EDID support for VESA/CEA, and custom timings

EDID support for VESA/CEA, and custom timings

- Automatic input acquisition and configuration

Automatic input acquisition and configuration

Product specifications**HDMI 2.0 QUAD INPUT CARD****General specifications**

Connectors	4x full sized HDMI™ connectors
Resolution	up to 2x 4096x2160@60p in '8L' slot
Color depth	8-bit; 10-bit; 12-bit (DL or lower)
Color sampling	up to UHD@60p 8-bit 4:4:4 or 10-bit 4:2:2
HDCP	HDCP 2.2 compliant
Signal capacity	600 MHz

Last updated: 19 Sep 2024

© 2024 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.