

# NGS-104

Communication and interface Module



## Product specifications

## NGS-104

### General specifications

---

Time code inputs	<ul style="list-style-type: none"><li>▪ 2 VITC signals<ul style="list-style-type: none"><li>• BNC input 75 Ohm</li><li>• SMPTE 12M-1999</li></ul></li><li>▪ 2 LTC signals (1 balanced, 1 unbalanced)<ul style="list-style-type: none"><li>• Phoenix 3-pin connector, BNC input 75 Ohm</li><li>• SMPTE 12M-1999 and EBU LTC compliant</li></ul></li></ul>
Serial interfaces	<ul style="list-style-type: none"><li>▪ 2 RS232/485/422</li><li>▪ DB9 connector</li><li>▪ Programmable communication protocol</li></ul>
Network interface	<ul style="list-style-type: none"><li>▪ 2x GbE connections for redundant streaming network connection</li><li>▪ Multicast streams - IGMP3.0 standards</li><li>▪ Metadata streams</li><li>▪ Control data</li></ul>
Power consumption	<ul style="list-style-type: none"><li>▪ Typical 25 Watt</li></ul>
Dimensions	<ul style="list-style-type: none"><li>▪ Utilizes one slot in an NGC chassis</li></ul>

---

Last updated: 08 Jul 2024

© 2024 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check [www.barco.com](http://www.barco.com) for the latest specifications.