

NIS-110

Nexxis Integration Server



- **On-site installation**
- **1 NIS-110 per hospital**
- **Simple configuration**
- **Designed for 24/7 operation**
- **Ready for NexxisCare deployment**

Inter-OR describes the capability to share video streams, and a central database, the NMS (Nexxis OR Management Suite) registry, between operating rooms.

The NIS-110, compatible with Nexxis 1.14 and later versions, makes the deployment of a large inter-OR setup easy and robust.

Product specifications**NIS-110****General specifications**

Operating system	Linux
Hardware configurations	Intel Core i5, 7th generation 16 GB RAM 256 GB industrial SSD
Nexxis integration	Fully integrated with Nexxis 1.14 and later versions
PSU	External PSU, 100-240VAC, 2A, 50-60Hz
Power consumption	Max: < 109W Typical: 83W
Size	60mm H x 190mm W x 190mm D
Weight	2,2 kg
Temperature	Operating: 0°C to 40°C (32°F to 104°F)
Humidity	Max 80%
Acoustic Noise	Typically 32dBA at 20°C at 1m
Mounting	A 19" rack mount can be purchased separately

Last updated: 08 Jul 2024

© 2024 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.