

MDSC-8156

56-inch Quad Full HD surgical display



The MDSC-8156 is a large-screen surgical display featuring a 56-inch LCD panel (16:9) with Quad Full HD resolution (3840 x 2160).

Perfect images in the surgical suite

The MDSC-8156 has been designed for use in interventional X-ray and cardiovascular suites, EP labs and hybrid operating rooms. The MDSC-8156 delivers accurate DICOM-compliant grayscale and color images with ultra-low latency, making it the preferred choice for interventional imaging.

Reliable and safe performance

The large-size, ultra high-resolution LCD screen offers a safer and more efficient alternative to multi-monitor configurations deployed in surgical environments. The redundant power supply architecture ensures stable and reliable operation in the most critical conditions.

Benefits:

- Ultra-high resolution (3840 x 2160 pixels)
- Versatile input configurations (4x Single link or 2x Dual link DVI)
- High brightness, high contrast ratio
- Low-latency video processing
- Redundant power supply system
- Laminated safety glass protection screen
- Medical-grade compliance
- 56-inch wide-screen color LCD with Quad Full HD resolution
- Wide viewing angle
- Advanced image processing algorithms
- DVI input connectivity for 4 x Single Link and 2 x Dual Link operating mode

Product specifications**MDSC-8156****General specifications**

Display technology	SMVA
Active area	1244 x 700 mm
Resolution	QFHD
Pixel density	3840 x 2160 Pixels x 3 colors
Aspect ratio	16:9
Brightness	450 cd/m ² typical
Contrast ratio	1500:1 (max.)
Response time	6,5 ms typical
Color depth	10 bit
Viewing angle	176° (H) , 176° (V) typical
Surface treatment	'Haze' type; hardness 3H
Color gamut	9300 K / 92% NTSC
Frame rate	60 Hz
Video inputs	Quad Single-Link DVI-D (HD)
Local Control	Keypad (5 keys, OSD assisted)
Remote control	Serial RS-232 (D-Sub9) or Serial Link over Ethernet (RJ45) selectable
Versions	MDSC-8156: "basic" (w/o glass & w/o redundant power supply) MDSC-8156 R: "light" (w/o glass & with redundant power supply) MDSC-8156 GR: "full" (with glass & with redundant power supply)
Power input	100 -240 Vac 50 / 60Hz
Power consumption	500 W typical (operating) 20 W typical (stand-by)
Operating temperature	+ 0 to +35 °C (operating) -20 to +60 °C (storage)
Operating humidity	
Dimensions	Width: 1345mm Height: 814 mm Depth: 150mm (GR version only)
Weight	75kg (with glass), 62kg (w/o glass)
Mounting	VESA 400
Approvals	IEC 60601-1, IEC 60601-1-2, EN 55011 -Class A, CISPR11 -Class A, EN55024, C-UL-US, FCC, CE

Last updated: 08 Jul 2024

© 2024 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.