

F10 AS3D

Compact Active Stereo DLP projector for professional applications



The F10 AS3D enables full 3D stereoscopic visualisation from a small, single lens chassis, and at full 120 Hz refresh rates commonly used in stereoscopic systems. Fully 1080p compatible, it is a tool not only for the scientific visualisation and simulation industries, but also suited for video and film production and DI and VFX creation. The revolutionary F10 AS3D offers full active 3D stereoscopic display at 120 fps refresh rates at all resolutions up to 1,920 x 1,200.

Unique high performance

The F10 AS3D runs full resolution at double the bandwidth – all the time. Hence, image quality, detail, and accuracy is much higher with the F10 AS3D.

Who's it for?

Designed primarily for the requirements of scientific visualization, simulation and mathematical modelling, it makes it easy to display 3D stereoscopic data analysis and other graphically challenging applications, such as design feasibility studies and modelling, not to mention 3D video and motion content.

Product specificaties

F10 AS3D

General specifications

Concept	single lens, dual head stereoscopic projector
Resolutie	SXGA+ (1400 x 1050)
Helderheid	Up to 2000 lumens (3D mode: up to 2000 ansi lumens 2D mode: up to 2000 ansi lumens)
Contrast	Up to 3000 : 1 (Prism-less optical design)
Technologie	patented 3D stereo technology single chip DLP display with fully active 3D stereo compatibility
Beeldverhouding	4:3 (SXGA+)
Beeldschermkleuren	30-bit RGB
Grafische indelingen computer	UXGA, SXGA+, SXGA, XGA, SVGA, VGA 1920x1080 -640 x 480 pixel resolution custom formats available RGBHV, RGBS, RGsB
Horizontale scanfrequenties	15 -150 kHz (resolution dependant)
Verticale scanfrequenties	48 -190 Hz (resolution dependant)
Videoformaten	EDTV (576p, 480p) SDTV (576i, 480i) HDTV (1080p, 1080i, 720p) NTSC, PAL, SECAM
Lenswerking	Focus and Manual zoom
Lenzen	Standard projection lens <ul style="list-style-type: none">▪ Lens number: EN08 / 503-0034-00▪ Focus range: 1.0 - 15.0 m▪ Throw ratio<ul style="list-style-type: none">• 1.73 - 2.17 : 1 (SXGA+) Wide Angle <ul style="list-style-type: none">▪ Lens number: EN10 / 503-0035-00▪ Focus range: 1.5 - 20.0 m▪ Throw ratio<ul style="list-style-type: none">• 1.03 : 1 (SXGA+)
Beeldbreedte	0.7 -2.5 m
Lichtbron	220W UHP
Levensduur lamp	Up to 2250 hours (Full power) Up to 3000 hours (Eco mode)
Computeringangen	2 x DVI-D 2 x VGA
Video-ingang	1 x YPbPr 1 x S-video 1 x Composite
Controlemogelijkheden	1 x RJ-45 TCP/IP 1 x 9-pin D-SUB RS232 1 x USB
Afmetingen	278 x 110 x 278 mm (WxHxD)
Gewicht	3.4 kg
Voedingsvereisten	5.0-1.7A ~100, 50-60Hz
Conformiteiten	CE, FCC Class A, UL, cUL and cCSAus
Bedrijfstemperatuur	0 -40 °C
Opslagtemperatuur	-20 -60 °C
Vochtigheid in bedrijf	20 -80% RH
Vochtigheid bij opslag	10 -90% RH
Kleur	Black metallic
(E)TSO	3 years, 500 hours or 90 days on lamp (whichever comes first).
BTU/uur	

Laatst bijgewerkt: 09 Jul 2024

© 2024 Barco nv. Alle rechten voorbehouden. Gehele of gedeeltelijke reproductie zonder schriftelijke toestemming is verboden. Alle merknamen en productnamen zijn handelsmerken, geregistreerde handelsmerken of handelsnamen van hun respectieve houders. Als gevolg van voortdurende innovatie kunnen informatie en technische specificaties zonder voorafgaande kennisgeving worden gewijzigd. Controleer www.barco.com voor de nieuwste specificaties.