

D-Cine DP60

... The Digital Cinema Experience



Технические характеристики**D-CINE DP60**

Общие характеристики	
Анаморфотные объективы	Optional Flat and Scope types attached via a twin lens adapter
Формирование сигналов цветности	Bit depth: 42 bit • Color Shades: 4.4 trillion • Color Gamut: 40% better than HDTV (similar to film)
Контрастность	1000:1 (full white / full black)
Охлаждение	Integrated 3 chip liquid cooling system and heat exchanger
Цифровое микрозеркальное устройство Digital MicroMirror Device™	3 x high resolution S-XGA DLP Cinema™ DMD™
Ввод цифрового видео	SMPTE 292M: Serial Digital Interface supporting formats: SMPTE 274M: 1920 x 1080 in 60Hz interlaced, 24P or 24 SF SMPTE 260M: 1920 x 1035 in 60Hz interlaced SMPTE 296M: 1280 x 720 in 60Hz progressive Note: interlaced sources to be encoded with 3:2 Pull-Down DFP Graphics port. Compatible with DVI standard.
Оправа	Cinemecanica OC7040H console
Освещение	Optional 2kW, 3kW, 5kW and 7kW Xenon Arc lamp depending on screen size.
Светоотдача	12fL up to 15 m (50ft.) wide (equivalent to 16fL open gate in a film projector). Brightness uniformity: within 90% over the entire screen area.
Местный контроль	• 4 x LED status indication: OK/ Touch Panel ready/Projector Head ready and Projector Error • 4 x push button control of digital head modes • 4 x user definable lamp house or automation controls • 4 x general purpose relays
Параметры	• Alternative Content Switcher And Router (ACSAR) Displays any incoming digital or analog signal, for HDTV movie and alternative digital cinema applications. • Automation Interface Compatible with industry standard automation systems • Touch Screen Remote Control For full control and diagnostics of the projector, the ACSAR and the automation functions. 19" rack and freestanding / wall mount options
Электропитание	US version Lamp power supply: 3-phase 208 V + N/60 Hz Digital head, cooling pump and touch screen: auto-ranging 80-240 V Lamp console: 110 V EUR Version Lamp power supply: 3-phase 400 V + N/50 Hz Digital head, cooling pump and touch screen: auto-ranging 80-240 V Lamp console: 220 V
Основные объективы	All focal lengths covered by a complete range of Isco Optic and Schneider zoom lenses
Рефлектор	Standard f2.0 dichroic glass type
Разрешение	1280 x 1024 per Red, Green and Blue channels; equivalent to 3.9 million pixels
Вес	Digital head and anamorphic lens holder (without lenses): 33 Kg / 72.7 lb.

Создано: 15 Mar 2023

Технические характеристики могут изменяться без предварительного уведомления. Для получения самой последней информации посетите веб-сайт www.barco.com.