
F80-4K7

7,000 lumens, 4K UHD, DLP laser phosphor projector





- Stunning images with superb color performance
- Ultimate installation flexibility
- 3D capable
- Silent operation

The stunning image quality and laser phosphor light source of Barco's F80 projectors enable you to provide exceptional experiences while saving both time and money. They're designed for fixed installation in a wide range of applications such as museums, board rooms, and auditoriums. Thanks to their 3D capability, they're also perfectly fit for theme park dark rides and interactive experiences.

Superior image quality

The F80-4K7 delivers stunning images with highly saturated colors that allow for accurate color reproduction at all times. What's more it features the powerful Barco Pulse processing that allows for sharper images and less latency thanks to its Single Step Processing (SSP).

Unprecedented business value

With this projector you can increase your uptime while driving costs down. Through its laser-phosphor light source and advanced cooling design, it provides a long operating time without need for lamp changes -resulting in considerable cost-savings on maintenance and consumables.

Ultimate installation flexibility

The F80-4K7 gives you more flexibility in projector location and orientation as it can run in any orientation. Thanks to its wide array of all-glass lenses and wide lens shift ranges, the F80-4K7 accommodates almost any projector configuration.



Product specifications	F80-4K7
General specifications	
Projector type	Single-chip DLP (0.67") laser phosphor projector
Resolution	3,840 x 2,400 (4K UHD) / 2,716 x 1,600 (WQXGA+ native)
Brightness	7,000 center lumen*
	0.000 11
	6,600 ansi lumen
	7,500 ISO lumen
Polish to the second to the se	0.007
Brightness uniformity Contrast ratio	> 90% 1,200:1 sequential, 10,000:1 dynamic *
Light source Light source lifetime	Laser phosphor > 20000 h in normal mode, > 12000 h in silent mode, > 40000 h in long life mode, > 12000 h in high brightness mode
Aspect ratio	2 20000 H in hormal mode, > 12000 H in silent mode, > 40000 H in long life mode, > 12000 H in high brightness mode
_ 	Rec. 709
Color space Orientation	360° rotation, no restrictions
Sealed DLP TM core	Yes
24/7 operation	Yes**
Color correction	P7 RealColor™
CLO (constant light output)	Yes
Keystone correction	Yes
Image processing	Embedded warp & blend engine
3D	Active stereoscopic 3D / Passive stereo compatible
Lens type	GLD/FLDX/FLD+(lens adapter needed)
Optical lens shift	Vertical up to 125%, depending on lens
	Horizontal up to 50%, depending on lens
	Motorized zoom and focus (with lens memory on GLD and FLDX lenses)
	Motorized lens shift (with position memory on all lenses)
Inputs	12G-SDI, 2x DP 1.2, 2x dual link DVI-D, HDBaseT, HDMI2.0 (HDCP2.2, HDR10), RJ 45 Ethernet, DMX in/out, RS232 in, 2x
	USB, 12V out
Input resolutions	Up to 4K UHD @ 60Hz / Up to 2,560 x 1,600 @ 120Hz
	refresh rates:
	24Hz to 120Hz for WQXGA+ (2716x1600) and 24Hz to 60Hz for 4K/4KUHD (4096 x 2160/ 3860 x 2400)
Software tools	Projector Toolset
Control	IR, RS232, RJ45, XLR wired
Network connection	10/100 Ethernet, RJ45
Power requirements	100-240V / 50-60Hz
Power consumption	700 W nominal, 850 W maximum
Standby power	
BTU per hour	2,400 BTU/h nominal, 2,900 BTU/h maximum
Noise level (typical at 25°C/77°F)	35 dB(A)
Operating temperature	10°C (50°F)-40°C (104°F) (up to 1500m altitude) / 10° (50°F) -35°C (95°F) (up to 3000m altitude)
Operating humidity	20 -80% RH (non-condensed)
Storage -transport temperature	-20 to 60 °C
Storage humidity	20 -90% RH (non-condensed)
Dimensions (WxLxH)	480 x 680 x 227 mm / 18.9 x 26.7 x 8.9 in
Weight	25.5 kg / 56.2 lbs
Standard accessories	Power cord, wireless remote control
Certifications	CE, FCC Class A, cNemkoUS, CCC, EAC, KSA, RCM, UkrSEPRO
Warranty *	Limited 3 years on parts and labor(***)
	Extendable up to 5 years.
	* When measured with the GLD 1.43-2.12:1 lens in Wide Angle ** For optimal performance, switch off the projector regularly. For details please consult the manual.
	*** Except on light source: 2000 hours in normal mode, or 3 years, whichever comes first.

Last updated: 30 May 2024

© 2024 Barco nv. Wszelkie prawa zastrzellone. Powielanie w callolici lub w czllici bez pisemnej zgody jest zabronione. Wszystkie nazwy marek i produktów sil znakami towarowymi, zastrzellonymi znakami towarowymi lub nazwami handlowymi odpowiednich wilalicicieli. Ze wzglildu na ciligile innowacje, informacje i specyfikacje techniczne mogii ulec zmianie bez wczeliniejszego powiadomienia. Sprawdii www.barco.com, aby uzyskali najnowsze specyfikacje.

