

ScenergiX Controller 2 x 2

ScenergiX Controller 3 X 1



- up to 4 addressable displays
4 fully configurable inputs
19 inch rack mount
Standard equipped with Xlite Toolset, controlling software.
Multipurpose device:
both Daylight Display and Projection
Arrange your sources onto your display through an intuitive interface.
Scale and position all sources exactly how you want them.
Overlay sources using advanced chroma-keying and alpha blending features.
Process video and data in pure quality onto your display.
Compatible with all standard image formats.

技術仕様

SCENERGIX CONTROLLER 2 X 2

一般仕様

入力	4 user defined inputs Front accessible Integrated video processing Auto sensing, hot swappable S-video, composite, YUV, RGB SDI, HD-SDI, DVI up to UXGA
互換性	Barco Daylight Displays Projectors
出力	four multifunctional outputs: DVI-A, DVI-D, RGB
制御	· Scaler 4 input channels [Data-Video] fully scalable to desired output resolution · Z-order Instant modification of Z-order control, for each output window · Window positioning Intuitive positioning interface · Connectors RS 232 [RJ11]
エフェクト	Anamorphic imaging Chroma-keying [per input] Alpha-keying [per input] Z-order control Windowing/View ports
動作温度	0° <> 45°
電力	240W-480W auto ranging 90-264V (50-60 Hz) Connector: 3 pin IEC
品番	R9851610

生成日:09 Jul 2024

© 2024 Barco nv.(C) Barco. All rights reserved. (無断転載を禁ず。) 書面による許可なく全部または一部を複製することは禁止されています。すべてのブランド名および製品名は、それぞれの所有者の商標、登録商標、または商号です。継続的な技術革新により、情報および技術仕様は予告なく変更される場合があります。最新の仕様についてはwww.barco.comをご確認ください。