iD R600+

SXGA+, 6,000 lumens single-chip DLP projector

BARCO

Especificações técnicas	ID R600+
Especificações gerais	
Saída de luz	6,000 ANSI lumens in dual lamp mode
Resolução	SXGA+ (1400 x 1050)
Uniformidade de brilho	> 95 % for the total screen
Razão de contraste	2,000 : 1 (full white/full black)
Visor	1-chip 0.95" DarkChip3® DLP® SXGA+ panel with BrilliantColor™ processing and a native resolution of 1400 x 1050 pixels, 4:3 aspect ratio
Recursos	▪ AutoImage ▪ Advanced picture-in-picture ▪ Seamless switching with effects ▪ Standard cable basket
Imagem em imagem	Up to 3 sources simultaneously (one of which can be video)
Entradas	▪ 1x Component Video, RGBHV, RGBS or RGsB (5 BNC) ▪ 1x Composite Video (BNC) ▪ 1x S-Video (4-pin mini-DIN) ▪ 1x VGA (D15 connector) ▪ 1x DVI (Digital Visual Interface) ▪ 1x SDI optional
Saída	No output
Comunicação	1x D9 connectors for RS232 In/Out 1x spherical IR receiver
Compatibilidade	▪ All current video sources (PAL, SECAM, NTSC) in Composite, S-VHS, Component or RGB formats ▪ All currently proposed HDTV, extended and improved television standards (1080i, 720p) ▪ All computer graphics formats from VGA, SVGA, XGA, SXGA to UXGA ▪ Most Macintosh computers ▪ Electronic workstations with a resolution up to 1600 x 1200 pixels at 75 Hz ▪ Most computer sources with a pixel clock up to 160 MHz ▪ DVI sources up to SXGA+
Compatibilidade de fonte de entrada	1600 x 1200 (max. input)
Tamanho da tela	From 1-6m / 3-20ft.
Frequências de Varredura	Horizontal 15kHz -110 kHz Vertical 25 Hz -150 Hz
Conexão de rede	Refer to iD Pro R600+
Lâmpada	2 x 250 Watt UHP lamp, in lamp housing, pre-aligned for max. light output. Typical lifetime: 1,500 h/lamp. 1,500 hours in Dual Lamp Mode or 3,000 hours in Single Lamp Mode.
Ótica	Sealed optical engine
Lentes	Fixed focal length lens with a throw ratio of 0.8:1 Variable focal length lenses with a throw distance of 1.1-1.3, 1.2-1.6, 1.6-2.4, 2.4-4.3 times the screen width
Deslocamento de Lente	Motorized V shift: -30% +110% For specific details per lens type: see lens product pages
Filtros de poeira	High Quality Microfilter (side removeable)
Nível de Ruído	< 39 dB
Tensão dos Cabos Elétricos	90V-255V
Consumo de energia	Max. 680 Watt
Dissipação de Potência	Max. 2400 BTU/hour
Energia de CA	Power factor pre-regulated SMPS, 90-254 VAC / 50-60Hz
Peso	Net weight: body only: 12.9 kg/28.5 lbs
Dimensões	Projector body with cable basket: 415 mm (max. W) x 195 mm (max. H) x 565 (max. D) Projector body without cable basket: 415 mm(max. W) x 195 mm (max. H) x 487 (max. D)
Regulamentos de Segurança	Em conformidade com UL1950 e EN60950
Interferência Eletromagnética	Compliant with FCC rules & regulations, part 15 Class B, CE EN55022 Class B and CCC

Gerada em: 09 Jul 2024

© 2024 Barco nv. Todos os direitos reservados. A reprodução total ou parcial sem permissão por escrito é proibida. Todos os nomes de marca e produto são marcas comerciais, marcas comerciais registradas ou nomes dos respectivos proprietários. Por causa da inovação contínua, as informações e as especificações técnicas estão sujeitas a alterações sem aviso prévio. Verifique www.barco.com para obter as especificações mais recentes.