

ScenergiX Controller 2 x 2

ScenergiX Controller 3 X 1



- up to 4 addressable displays
4 fully configurable inputs
19 inch rack mount
Standard equipped with Xlite Toolset, controlling software.
Multipurpose device: both Daylight Display and Projection
Arrange your sources onto your display through an intuitive interface. Scale and position all sources exactly how you want them. Overlay sources using advanced chroma-keying and alpha blending features. Process video and data in pure quality onto your display. Compatible with all standard image formats.

Product specifications**SCENERGIX CONTROLLER 2 X 2**

General specifications	
Input	4 user defined inputs Front accessible Integrated video processing Auto sensing, hot swappable S-video, composite, YUV, RGB SDI, HD-SDI, DVI up to UXGA
Compatibility	Barco Daylight Displays Projectors
Output	four multifunctional outputs: DVI-A, DVI-D, RGB
Control	· Scaler 4 input channels [Data-Video] fully scalable to desired output resolution · Z-order Instant modification of Z-order control, for each output window · Window positioning Intuitive positioning interface · Connectors RS 232 [RJ11]
Effects	Anamorphic imaging Chroma-keying [per input] Alpha-keying [per input] Z-order control Windowing/ View ports
Operating T°	0° <> 45°
Power	240W-480W auto ranging 90-264V (50-60 Hz) Connector: 3 pin IEC
Order Information	R9851610

Last updated: 15 Mar 2023

© 2018 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.