

iQ R500

SXGA+, 5,000 lumens LCD projector



Product specifications

IQ R500

General specifications

Light output	5,000 ANSI lumens
Resolution	SXGA+ (1400 x 1050)
Brightness uniformity	> 95 % for the total screen
Contrast ratio	> 800:1 (full white/full black)
Display	3 active matrix 1.4" diagonal SXGA+ polysilicon LCD panels with Micro Lens Arrays and a resolution of 1400 x 1050 pixels (aspect ratio 4:3). LCD panels are selected for a minimum of pixel defects.
Features	<ul style="list-style-type: none">AutolmageAdvanced picture-in-pictureSeamless switching with effectsStandard cable basketStandard light shutterAdvanced digital zoom
Picture-in-picture	Up to 4 sources simultaneously (2 data, 1 video and 1 SDI)
Inputs	<ul style="list-style-type: none">1x Configurable 5-Wire (BNC) for: Composite Video, S-Video, Component Video, RGBHV, RGBS, RGsB1x Composite Video (BNC) (up to 7 Composite Video's when using all connectors on top input board)1x S-Video (4-pin mini-DIN) (up to 3 S-Video's when combining BNC's)1x VGA (D15 connector)1x DVI (Digital Visual Interface)
Communication	1x D9 connectors for RS232 In/Out 1x spherical IR receiver
Compatibility	<ul style="list-style-type: none">All current video sources (PAL, SECAM, NTSC) in Composite, S-VHS, Component or RGB formatsAll currently proposed HDTV, extended and improved television standards (1080i, 720p)All computer graphics formats from VGA, SVGA, XGA, SXGA to UXGAMost Macintosh computersElectronic workstations with a resolution up to 1600 x 1200 pixels at 60 HzMost computer sources with a pixel clock up to 160 MHzDVI sources up to SXGA+
Input source compatibility	1600 x 1200 (max. input)
Screen size	From 1-6m / 3-20ft.
Scan Frequencies	Horizontal 15kHz -110 kHz Vertical 25 Hz -150 Hz
Network connection	Refer to IQ Pro R500
On board display server	Refer to IQ Pro R500
Ambient temperature	5°C up to 40°C
Lamp	2x 250 Watt UHP lamp, in lamp housing, pre-aligned for max. light efficiency. Typical lamp system lifetime: Full Power Mode: 1,500 hrs (3,000 hrs in single lamp mode) Economy Mode: 3,000 hrs (6,000 hrs in single lamp mode)
Lenses	Fixed focal length lenses are available with a throw ratio of 0.85:1 (very short throw ratio, specially designed for rear screen on-axis projection) or 7.0:1 (long throw). Variable focus lenses with a throw distance of 1.3-1.8, 1.9-2.6, 3.0-6.0 times the screen width (2.5% tolerance)
Lens Shift	Motorized V shift: -30% +110%
Dust filters	For specific details per lens type: see lens product pages
Noise Level	High Quality Microfilter (side removeable) < 38dB
Mains Voltage	90V-255V
Power consumption	Max. 620 Watt
Power Dissipation	Max 2300 BTU/h
AC power	Power factor pre-regulated SMPS, 90-254 VAC / 50-60Hz
Weight	Net weight: Body only 12.9kg / 28.5 lbs. Shipping weight: • without lens: max.17.5 kg / 28.5 lbs. • with lens: max. 20 kg / 44 lbs.
Dimensions	Projector body with cable basket: 415 mm (max. W) x 195 mm (max. H) x 565 (max. D) Projector body without cable basket: 415 mm(max. W) x 195 mm (max. H) x 487 (max. D)
Safety Regulations	Compliant with UL1950 and EN60950
Electromagnetic Interference	Compliant with FCC rules & regulations, part 15 Class B and CE EN55022 Class B

Last updated: 09 Jul 2024

© 2024 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.