F80-Q7

7,000 lumens, WQXGA, DLP laser phosphor projector



- Stunning images with superb color performance
- Ultimate installation flexibility
- 3D capable



The stunning image quality and laser phosphor light source of Barco's F80 projectors enable you to provide exceptional experiences while saving both time and money. They're designed for fixed installation in a wide range of applications such as museums, board rooms, and auditoriums. Thanks to their 3D capability, they're also perfectly fit for theme park dark rides and interactive experiences.

Superior image quality

The F80-Q7 delivers stunning images with highly saturated colors that allow for accurate color reproduction at all times. What's more it features the powerful Barco Pulse processing that allows for sharper images and less latency thanks to its Single Step Processing (SSP).

Unprecedented business value

With this projector you can increase your uptime while driving costs down. Through its laser-phosphor light source and advanced cooling design, it provides a long operating time without need for lamp changes -resulting in considerable costsavings on maintenance and consumables.

Ultimate installation flexibility

The F80-Q7 gives you more flexibility in projector location and orientation as it can run in any orientation. Thanks to its wide array of all-glass lenses and wide lens shift ranges, the F80-Q7 accommodates almost any projector configuration.



Single-chip DLP (0.67') laser phosphor projector 2.716 x 1.600 (WQXGA+ native) 7,000 center lumen* 6,600 ansi lumen 7,500 ISO lumen > 90% 1.200:1 sequential, 10,000:1 dynamic* Laser phosphor > 20000 h in normal mode, > 12000 h in silent mode, > 40000 h in long life mode, > 12000 h in high brightness mode 16:10 Rec. 709 360* rotation, no restrictions Yes Yes** P7 RealColor™ Yes Yes Yes Yes Embedded warp & blend engine Active stereoscopic 3D / Passive stereo compatible
2,716 x 1,600 (WQXGA+ native) 7,000 center lumen* 6,600 ansi lumen 7,500 ISO lumen > 90% 1,200:1 sequential, 10,000:1 dynamic* Laser phosphor > 20000 h in normal mode, > 12000 h in silent mode, > 40000 h in long life mode, > 12000 h in high brightness mode 16:10 Rec. 709 360° rotation, no restrictions Yes Yes Yes Yes Yes Yes Yes Ye
7,000 center lumen* 6,600 ansi lumen 7,500 ISO lumen > 90% 1,200:1 sequential, 10,000:1 dynamic* Laser phosphor > 20000 h in normal mode, > 12000 h in silent mode, > 40000 h in long life mode, > 12000 h in high brightness mode 16:10 Rec. 709 360° rotation, no restrictions Yes Yes Yes Yes Yes Yes Yes Ye
 6,600 ansi lumen 7,500 ISO lumen > 90% 1,200:1 sequential, 10,000:1 dynamic* Laser phosphor > 20000 h in normal mode, > 12000 h in silent mode, > 40000 h in long life mode, > 12000 h in high brightness mode 16:10 Rec. 709 360° rotation, no restrictions Yes Yes** P7 RealColor™ Yes Yes Yes Yes Yes Yes Yes Embedded warp & blend engine
7,500 ISO lumen > 90% 1,200:1 sequential, 10,000:1 dynamic* Laser phosphor > 20000 h in normal mode, > 12000 h in silent mode, > 40000 h in long life mode, > 12000 h in high brightness mode 16:10 Rec. 709 360° rotation, no restrictions Yes Yes Yes P7 RealColor™ Yes Yes Embedded warp & blend engine
7,500 ISO lumen > 90% 1,200:1 sequential, 10,000:1 dynamic* Laser phosphor > 20000 h in normal mode, > 12000 h in silent mode, > 40000 h in long life mode, > 12000 h in high brightness mode 16:10 Rec. 709 360° rotation, no restrictions Yes Yes Yes P7 RealColor™ Yes Yes Embedded warp & blend engine
 > 90% 1,200:1 sequential, 10,000:1 dynamic* Laser phosphor > 20000 h in normal mode, > 12000 h in silent mode, > 40000 h in long life mode, > 12000 h in high brightness mode 16:10 Rec. 709 360° rotation, no restrictions Yes Yes Yes** P7 RealColor™ Yes Yes Yes Yes Yes Yes Embedded warp & blend engine
1,200:1 sequential, 10,000:1 dynamic* Laser phosphor > 20000 h in normal mode, > 12000 h in silent mode, > 40000 h in long life mode, > 12000 h in high brightness mode 16:10 Rec. 709 360° rotation, no restrictions Yes P7 RealColor™ Yes Yes Embedded warp & blend engine
1,200:1 sequential, 10,000:1 dynamic* Laser phosphor > 20000 h in normal mode, > 12000 h in silent mode, > 40000 h in long life mode, > 12000 h in high brightness mode 16:10 Rec. 709 360° rotation, no restrictions Yes P7 RealColor™ Yes Yes Embedded warp & blend engine
Laser phosphor > 20000 h in normal mode, > 12000 h in silent mode, > 40000 h in long life mode, > 12000 h in high brightness mode 16:10 Rec. 709 360° rotation, no restrictions Yes Yes P7 RealColor™ Yes Yes Embedded warp & blend engine
 > 20000 h in normal mode, > 12000 h in silent mode, > 40000 h in long life mode, > 12000 h in high brightness mode 16:10 Rec. 709 360° rotation, no restrictions Yes Yes** P7 RealColor™ Yes Yes Yes Embedded warp & blend engine
16:10 Rec. 709 360° rotation, no restrictions Yes Yes** P7 RealColor™ Yes Yes Yes Embedded warp & blend engine
Rec. 709 360° rotation, no restrictions Yes Yes** P7 RealColor™ Yes Yes Yes Embedded warp & blend engine
360° rotation, no restrictions Yes Yes** P7 RealColor™ Yes Yes Embedded warp & blend engine
Yes Yes** P7 RealColor™ Yes Yes Embedded warp & blend engine
Yes** P7 RealColor™ Yes Yes Embedded warp & blend engine
P7 RealColor™ Yes Yes Embedded warp & blend engine
Yes Yes Embedded warp & blend engine
Yes Embedded warp & blend engine
Embedded warp & blend engine
Active stereoscopic 3D / Passive stereo compatible
GLD/FLDX/FLD+(lens adapter needed)
Vertical up to 125%, depending on lens
Horizontal up to 50%, depending on lens
Motorized zoom and focus (with lens memory on GLD and FLDX lenses)
Motorized lens shift (with position memory on all lenses)
12G-SDI, 2x DP 1.2, 2x dual link DVI-D, HDBaseT, HDMI2.0 (HDCP2.2, HDR10), RJ 45 Ethernet, DMX in/out, RS232 in, 2x USB, 12V out
Up to 4K UHD @ 60Hz / Up to 2,560 x 1,600 @ 120Hz
refresh rates:
24Hz to 120Hz for WQXGA+ (2716x1600) and 24Hz to 60Hz for 4K/4KUHD (4096 x 2160/ 3860 x 2400)
Projector Toolset
IR, RS232, RJ45, XLR wired
10/100 Ethernet, RJ45
100-240V / 50-60Hz
700 W nominal, 850 W maximum
2,400 BTU/h nominal, 2,900 BTU/h maximum
35 dB(A)
10°C (50°F)-40°C (104°F) (up to 1500m altitude) / 10° (50°F) -35°C (95°F) (up to 3000m altitude)
20 -80% RH (non-condensed)
-20 to 60 °C
20 -90% RH (non-condensed)
480 x 680 x 227 mm / 18.9 x 26.7 x 8.9 in
25.5 kg / 56.2 lbs
Power cord, wireless remote control
CE, FCC Class A, cNemkoUS, CCC, EAC, KSA, RCM, UkrSEPRO
Limited 3 years on parts and labor(***)
Extendable up to 5 years.
* When measured with the GLD 1.43-2.12:1 lens in Wide Angle
** For optimal performance, switch off the projector regularly. For details please consult the manual. *** Except on light source: 20,000 hours in normal mode, or 3 years, whichever comes first.

Last updated: 30 May 2024

© 2024 Barco nv. Wszelkie prawa zastrzellone. Powielanie w callolici lub w czlilici bez pisemnej zgody jest zabronione. Wszystkie nazwy marek i produktów sli znakami towarowymi, zastrzellonymi znakami towarowymi lub nazwami handlowymi odpowiednich wlalicicieli. Ze wzglildu na ciligile innowacje, informacje i specyfikacje techniczne mogli ulec zmianie bez wczeliniejszego powiadomienia. Sprawdli www.barco.com, aby uzyskali najnowsze specyfikacje.

BARCO