

# S3 Standalone

Compact Event Master processor



Update August 2021: With the release of the S3-4K empty chassis this S3-4K Standalone configuration will no longer be available once existing stock is consumed (first come, first served) and we will move fully into Build-to-order (BTO). We will continue to build the S3-4K Jr. and the S3-4K Tri-combo configurations.

With up to 12 HD inputs and 12 outputs, the S3 Standalone brings the power of the S3-4K processor to your applications that require less capacity. The S3 Standalone removes the linking capability of the S3-4K, but keeps all of the inputs, outputs, and layers. In the field it offers you the same processing performance, image quality and rugged durability. In short: all the tools you need to create a stunning live experience for clearly-defined projects and fixed installs. Being modular and upgradeable, if you need to link, simply install the linking card and the S3 standalone becomes a full S3-4K.

### Powerful, easy, compact

- Modular card-based design
- Easy set-up with the cross-platform Event Master Toolset, providing a step-by-step approach to system configuration
- Dual, redundant power supplies for maximum peace of mind
- Widescreen blending support
- Interlinking available as an option

## Product specificaties

## S3 STANDALONE

### General specifications

Model	NGS-3U
Live-effectencanvas	Up to 20 megapixels in PVW/PGM or 40 megapixels in PGM only mode
Video-ingangen	12 HD inputs via 3 input cards (Event Master series cards) <ul style="list-style-type: none"><li>Up to 3x 4K inputs - each input card supports up to 4K@60p</li><li>4x SD/HD/3G SDI</li><li>4x HDMI 1.4a (297 MHz max)</li><li>4x DisplayPort 1.1 (300 MHz max)</li></ul>
Video-uitgangen	12 HD outputs via 3 output cards (Event Master Series Cards) <ul style="list-style-type: none"><li>Up to 3x 4K outputs - each output card supports up to 4K@60 p</li><li>4x SD/HD/3G SDI</li><li>4x HDMI 1.4a (297 MHz max)</li><li>2x HDMI 1.4a for Multiviewer (297 MHz max) or 4x HDMI 1.4a when used as standard output card</li></ul>
Genlock	Analog reference input/loop on BNC connectors; bi-level and blackburst at SD and tri-level at HD S3D Sync: 4x input Din connector, 2x output Din connector
Programma-uitvoer	Up to 8 program outputs configurable as single screens or tiled/blended widescreens (preview and Multi-Viewer not available in all configurations). Configurable for up to 8x 2048x1200@60 or up to 3x 4096x2400@60 outputs supporting Aux or Program destinations Independent edge blending/feathering control for all four sides.
Aux-uitgangen met schaalverdeling	User-definable from 12x 2048x1200@60 to 3x 4K@60 All outputs can be defined as Aux destinations for a total of 12 Aux outputs Output color correction
Mixers	<ul style="list-style-type: none"><li>Native resolution background mixer per output screen</li><li>Independent layer transitions or full Preview/Program transition</li><li>Flexible layer allocation – 4 mixable or 8 single scalable PIP/key layers assignable to any Program output screen</li></ul>
Geheugenruimte voor foto's	Up to 100 HD or 25 UHD, depending on the import file size.
Laageffecten	<ul style="list-style-type: none"><li>Borders (hard, soft, halo) and drop shadows</li><li>Color effects</li><li>Strobe, H&amp;V flip</li><li>Luma, chroma and Cut/Fill keys (not all modes support keying)</li><li>PIP moves via Keyframes</li></ul>
Multiviewer	<ul style="list-style-type: none"><li>Flexible user-definable layouts</li><li>Monitor all Inputs and Outputs, including Preview and Aux</li><li>Two outputs</li><li>Dedicated hardware same as E2 Event Master Processor</li></ul>
Uitbreidbaarheid	Linking is available as an upgrade option
HDCP	HDCP compliance determined by installed cards.
Controle	<ul style="list-style-type: none"><li>Event Master screen management software for PC or Mac</li><li>Event Master Controllers</li><li>WebUI</li><li>Ethernet RJ-45, 1000/100/10 Mbps autosense</li></ul>
Onderhoudsgemak	Field-serviceable I/O and processing cards (not hot-swappable)  Hot swappable dual-redundant power supplies (optional)
Geluidsniveau	Max 51.3 dB avg. Fans at 100%. Fan speed is software-managed based on operating temperature. Reference ISO 7779
Afmetingen	<ul style="list-style-type: none"><li>Height: 13.26 cm / 5.22" - 3 RU rack mount</li><li>Width: 43.2 cm / 17" without chassis handles, 48.3 cm / 19" with chassis handles attached</li><li>Depth: 54 cm / 21.33" overall</li></ul>
Gewicht	21.3 kg / 47 lbs
Vermogen	Input power: 100-240 VAC 50/60Hz 826 Watt Ships with single power supply. Optional Dual-redundant, hot-swappable power supplies available as upgrade.
Omgevingstemperatuur	0-40° C (32-104° F)
Omgevingsvochtigheid	0-95% non-condensing (non-operating) 0-85% non-condensing (operational)
Garantie	3 years parts and labor

Laatst bijgewerkt: 09 Jul 2024

© 2024 Barco nv. Alle rechten voorbehouden. Gehele of gedeeltelijke reproductie zonder schriftelijke toestemming is verboden. Alle merknamen en productnamen zijn handelsmerken, geregistreerde handelsmerken of handelsnamen van hun respectieve houders. Als gevolg van voortdurende innovatie kunnen informatie en technische specificaties zonder voorafgaande kennisgeving worden gewijzigd. Controleer [www.barco.com](http://www.barco.com) voor de nieuwste specificaties.