

SP4K-35B

35,000 lumens smart cinema projector



- **Brilliant image**
- **Ready for tomorrow, today**
- **Barco EcoPure™**
- **Fit and forget**

SP4K-35B is part of the Series 4 portfolio, designed in close collaboration with industry partners. Market trends in content creation, exhibition and technology were taken into account. The result? A 4K RGB projector family, designed for cinema. The SP4K models come in many different configurations offering you the freedom of choice. A range of lumens, compatibility with both Barco lenses and selected 3rd party lenses, and optional touch displays. Play with the available options to match your specific needs.

Brilliant image

The Series 4 brings native 4K resolution, higher contrast and enhanced uniformity into the movie theater. The Barco Active Image Management™ and its patented precision brightness technology guarantees flawless images with automatic white balances.

Ready for tomorrow, today

The Barco Colorgenic™ technology opens up the full P3 color space and more than 98.5% of Rec. 2020. SP4K-35B is fully enabled for future innovations like 4K 120fps and HDR images. Deliver stunning results not only on day 1, but consistently throughout the lifetime of the product.

Barco EcoPure™

This silent running projector (51dB(A)) is fully ready for boothless operation. In addition, the SP4K-35B smartly manages its power consumption resulting in a high projector efficiency of 11.3 lm/W. In eco-mode it consumes even less than 3 Watt. What's more, remote wake up on LAN is possible for scheduled maintenance or ingest.

Fit and forget

The modular design of the Series 4 projectors allows for cost-effective maintenance. There are only six Barco laser plate™ spare parts to service all light source configurations. Anyone can replace the filters thanks to the toolless cover and filter handling. The SP4K-35B seamlessly integrates into your current setup.

Product specifications**SP4K-35B**

| General specifications | |
|--------------------------------|--|
| Native brightness | 35,000 lumens (typical) |
| Native contrast ratio | 2000:1 (typical) |
| Digital MicroMirror Device™ | 3x 1.38" DC4K |
| Resolution | native 4K: 4096 x 2160 |
| Color gamut | DCI P3 (98.5% of Rec. 2020; when measured in xy-color coordinates) |
| Light source | Laser |
| Prime lenses | 1.13-1.72; 1.35-1.86; 1.46-2.10; 1.65-2.60; 2.00-3.35; 2.53-4.98 High-brightness and high-contrast B-lenses compatible |
| Long-term brightness stability | 40,000 hrs @ average usage conditions |
| Housing | integrated cooling design and patented sealed optical assembly |
| Dimensions (WxLxH) | projector incl. feet 760 x 1470 x 612 mm 29,92 x 57,54 x 24,09 inches |
| Weight | 163kg/359lbs |
| Power requirements | single phase or triple phase 200-240V 20A |
| Heat load (max. power) | 10,000 BTU/hr |
| Exhaust airflow | 615CFM |
| Ambient temperature | 40°C / 104F max. |
| Ambient humidity | 85% RH max. |
| Media server | Barco Alchemy ICMP-X and other media server brands ** supported |
| Power consumption | 3.1kW (3W in Eco mode) |
| Noise Level | 51dB(A) @1m and 25°C ambient temperature |
| 3D systems | Active glasses systems and polarization systems on silver screens are supported. Color separation systems are not supported. |
| Safety requirements | Class 1 risk group 3 |
| User interface | Touch Display and/or web based |
| Notes | ** projector configuration with ICP-D; contact Barco service for the list of supported brands |

Last updated: 09 Apr 2024

© 2018 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.