

Fiber output card



- Integrated 12G/6G/3G over Fiber (SMPTE 297M)
- Support for output rotation of 90,180, or 270 degrees
- Rugged modular design
- Integrated fiber extender
- 4k@60p with optical fiber output using SFP+
- Standards based fiber extension using SMPTE 297M for Optical Fiber SDI
- Supports up to (1) 12G, (1) 6G or (2) 3G outputs
- Mirrored 4k@60 output for redundancy
- Support for output rotation of 90,180, or 270 degrees
- Rugged modular design
- Transceivers/SFP Modules sold separately

Product specifications**FIBER OUTPUT CARD**

General specifications	
Connectors	2x SFP+ (transceivers sold separately)
Resolution	Up to 1x 4096x2160p60 or 2x 1920x1080p60
Color depth	8-bit; 10-bit
Color sampling	12G-SDI up to UHD@60p 4:2:2 10-bit
HDCP	not supported
Signal capacity	12G/6G/3G SDI
Features	Rotation and splitter mode

Last updated: 15 Mar 2023

© 2018 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.