

RLM G5 Performer

With its compact design and sealed optics, the RLM G5 Performer is an ideal all-round projector suitable to both the rental as staging markets.



技术规格

RLM G5 PERFORMER

一般规格

光输出	4000 ANSI Lumen																								
分辨率	1024 x 768 (native)																								
对比度	900 : 1 (full field)																								
高对比度模式	Available with special lenses																								
亮度均匀性	> 90%																								
灯泡	2 x 250 W mercury																								
	max. lifetime: 1500 hrs typ. lifetime: 1000 hrs min. lifetime: 750 hrs																								
噪音级别 (@ 20°C - 68°F)	< 42 dBa																								
噪音等级 (@ 40°C - 104°F)																									
环境温度	Max 40°C (104°F)																								
功率消耗	700 W																								
电源电压	92-240 V																								
净重	Projector: 25 kg (56 lbs) Frame: 5 kg (11 lbs)																								
尺寸(宽x长x高)	705 x 707,8 x 316,5 mm																								
灯快门装置	Standard																								
封装DLP™内核	Standard																								
ScenergiX	Standard horizontal and vertical electronic edge blending																								
无缝切换	Standard (wipes, fades, ...)																								
画中画	Up to 4 sources simultaneously (2 data, 1 video and 1 SDI)																								
数字变焦	Standard																								
镜头编码器	On zoom and focus (with TLD lenses)																								
联动恒定光输出	not available																								
输入源兼容性	1600 x 1200 (max. input)																								
固定输入	<ul style="list-style-type: none"> ▪ 1x configurable 5 cable (BNC) ▪ 1x composite Video (BNC) ▪ 1x S-Video (4-pin DIN) ▪ 1x analogue RGB (D15 Connector) ▪ 1x SDI (+ loop through) ▪ 1x DVI (Digital Visual Interface) 																								
模块化输入	not available																								
控制	<ul style="list-style-type: none"> ▪ 1 x RS-232 / 422 IN ▪ 1 x XLR female (2 way) ▪ build-in RF remote transceiver (optional) 																								
移动范围	<table border="1"> <thead> <tr> <th>Lens</th> <th>Shift Range</th> </tr> </thead> <tbody> <tr> <td>RLD 0.8</td> <td>up-down: 25<->25 left-right: 20<->20</td> </tr> <tr> <td>Other RLD</td> <td>up-down: 100<->10 left-right: 75<->75</td> </tr> <tr> <td>TLD HB 0.8</td> <td>up-down: 60<->35 left-right: 50<->50</td> </tr> <tr> <td>Other TLD HB</td> <td>up-down: 120<->25 left-right: 75<->75</td> </tr> </tbody> </table>	Lens	Shift Range	RLD 0.8	up-down: 25<->25 left-right: 20<->20	Other RLD	up-down: 100<->10 left-right: 75<->75	TLD HB 0.8	up-down: 60<->35 left-right: 50<->50	Other TLD HB	up-down: 120<->25 left-right: 75<->75														
Lens	Shift Range																								
RLD 0.8	up-down: 25<->25 left-right: 20<->20																								
Other RLD	up-down: 100<->10 left-right: 75<->75																								
TLD HB 0.8	up-down: 60<->35 left-right: 50<->50																								
Other TLD HB	up-down: 120<->25 left-right: 75<->75																								
投射比例	<table border="1"> <thead> <tr> <th>Lens</th> <th>Throw ratio</th> </tr> </thead> <tbody> <tr> <td>RLD 0.8</td> <td>0.8</td> </tr> <tr> <td>RLD 1.5 - 1.8</td> <td>1.5 - 1.8</td> </tr> <tr> <td>RLD 1.8 - 2.25</td> <td>1.8 - 2.25</td> </tr> <tr> <td>RLD 2.25 - 3.0</td> <td>2.25 - 3.0</td> </tr> <tr> <td>RLD 3.0 - 4.5</td> <td>3.0 - 4.5</td> </tr> <tr> <td>RLD 4.5 - 7.0</td> <td>4.5 - 7.0</td> </tr> <tr> <td>TLD HB 0.8</td> <td>1.0</td> </tr> <tr> <td>TLD HB 1.6 - 2.0</td> <td>2.0 - 2.5</td> </tr> <tr> <td>TLD HB 2.0 - 2.8</td> <td>2.5 - 3.5</td> </tr> <tr> <td>TLD HB 2.8 - 5.0</td> <td>3.5 - 6.3</td> </tr> <tr> <td>TLD HB 5.0 - 8.0</td> <td>6.3 - 10.0</td> </tr> </tbody> </table>	Lens	Throw ratio	RLD 0.8	0.8	RLD 1.5 - 1.8	1.5 - 1.8	RLD 1.8 - 2.25	1.8 - 2.25	RLD 2.25 - 3.0	2.25 - 3.0	RLD 3.0 - 4.5	3.0 - 4.5	RLD 4.5 - 7.0	4.5 - 7.0	TLD HB 0.8	1.0	TLD HB 1.6 - 2.0	2.0 - 2.5	TLD HB 2.0 - 2.8	2.5 - 3.5	TLD HB 2.8 - 5.0	3.5 - 6.3	TLD HB 5.0 - 8.0	6.3 - 10.0
Lens	Throw ratio																								
RLD 0.8	0.8																								
RLD 1.5 - 1.8	1.5 - 1.8																								
RLD 1.8 - 2.25	1.8 - 2.25																								
RLD 2.25 - 3.0	2.25 - 3.0																								
RLD 3.0 - 4.5	3.0 - 4.5																								
RLD 4.5 - 7.0	4.5 - 7.0																								
TLD HB 0.8	1.0																								
TLD HB 1.6 - 2.0	2.0 - 2.5																								
TLD HB 2.0 - 2.8	2.5 - 3.5																								
TLD HB 2.8 - 5.0	3.5 - 6.3																								
TLD HB 5.0 - 8.0	6.3 - 10.0																								
订购信息	R9010021																								

生成于: 09 Jul 2024

© 2024 巴可公司。保留所有权利。未经书面许可, 禁止全部或部分复制。所有品牌名称和产品名称均为其各自持有者的商标、注册商标或商号。由于不断创新, 信息和技术规格如有变更, 恕不另行通知。请查看www.barco.com.cn以了解最新规格。