

iD Pro R600

The smartest and brightest network centric single-chip DLP projector with SXGA+ resolution and an amazing brightness level of 6,000 ANSI lumens.



Product specifications

ID PRO R600

General specifications

Light output	6,000 ANSI lumens
Resolution	SXGA+ (1400 x 1050)
Brightness uniformity	> 95 % for the total screen
Contrast ratio	2,000 : 1 (full white/full black)
Display	1-chip 0.95" DarkChip3™ DLP™ SXGA+ panel, with a native resolution of 1400 x 1050 pixels, 4:3 aspect ratio
Features	<ul style="list-style-type: none">AutolmageAdvanced picture-in-pictureSeamless switching with effectsStandard cable basket
Picture-in-picture	Up to 3 sources simultaneously
Inputs	<ul style="list-style-type: none">1x Component Video (RGBHV, RGBS or RGsB (5 BNC))1x Composite Video (BNC)1x S-Video (4-pin mini-DIN)1x VGA (D15 connector)1x DVI (Digital Visual Interface)1x SDI optional <p>Audio connections:</p> <ul style="list-style-type: none">1x Stereo mic in1x Stereo line in1x Stereo line out
Outputs	No output
Communication	1x D9 connectors for RS232 In/Out 1x spherical IR receiver
Compatibility	<ul style="list-style-type: none">All current video sources (PAL, SECAM, NTSC) in Composite, S-VHS, Component or RGB formatsAll currently proposed HDTV, extended and improved television standards (1080i, 720p)All computer graphics formats from VGA, SVGA, XGA, SXGA to UXGAMost Macintosh computersElectronic workstations with a resolution up to 1600 x 1200 pixels at 75 HzMost computer sources with a pixel clock up to 160 MHzDVI sources up to SXGA+
Input source compatibility	1600 x 1200 (max. input)
Screen size	From 1-6m / 3-20ft.
Scan Frequencies	Horizontal 15kHz -110 KHz Vertical 25 Hz -150 Hz
Network connection	1 x 10/100 Base-T Ethernet
On board display server	Server Specifications: -Processor: Pentium M 1.6 GHz -Memory: 512 MB DDR RAM -Storage: 40 GB hard disk -Inputs and outputs: <ul style="list-style-type: none">PCMCIA slot for Wireless LAN cards, memory cards, Bluetooth, input extensions ...RJ45connector for Ethernet (10Mb/s) and Fast Ethernet (100Mb/s)4 USB connectorsAudio: 3,5 mm jacks for Microphone in, Line in and Line out
Ambient temperature	5°C up to 40°C
Lamp	2 x 250 Watt UHP lamp, in lamp housing, pre-aligned for max. light output. Typical lifetime: 1,500 h/lamp. 1,500 hours in Dual Lamp Mode or 3,000 hours in Single Lamp Mode.
Lenses	Fixed focal length lens with a throw ratio of 0.8:1 Variable focal length lenses with a throw distance of 1.1-1.3, 1.2-1.6, 1.6-2.4, 2.4-4.3 times the screen width
Lens Shift	Motorized V shift: -30% +110%
Lens encoders	For specific details per lens type: see lens product pages
ScenergiX	Not Applicable
Sealed DLP™ core	Not Applicable
Dust filters	High Quality Microfilter (side removeable)
Noise Level	< 41 dB
Mains Voltage	90V-255V
Power consumption	Max. 680 Watt
Power Dissipation	Max. 2400 BTU/hour
AC power	Power factor pre-regulated SMPS, 90-254 VAC / 50-60Hz
Weight	Net weight: body only: 13.5 kg/29.8 lbs
Dimensions	Projector body with cable basket: 415 mm (max. W) x 195 mm (max. H) x 565 (max. D) Projector body without cable basket: 415 mm(max. W) x 195 mm (max. H) x 487 (max. D)
Safety Regulations	Compliant with UL1950 and EN60950
Electromagnetic Interference	Compliant with FCC rules & regulations, part 15 Class B, CE EN55022 Class B and CCC

Last updated: 09 Jul 2024

© 2024 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check www.barco.com for the latest specifications.