

MNA-440 ENC SDI

4K AV-to-IP adapter for the OR and hybrid OR



- AV-to-IP conversion
- Up to 4K resolution
- Medical-grade
- Established 3rd generation technology

Adapter for the operating room

The MNA-440 ENC SDI converts 2x 3GSDI or 1x 12GSDI or 1x QUAD SDI video signals to Nexxis RAW IP packets. Other non-video signals such as audio and USB for keyboard/mouse are also supported. End-to-end video latency is amazingly low and is guaranteed not to exceed a single frame. The video streams that are distributed over the Nexxis network can go up to a resolution of 4K.

Capabilities

The MNA-440 adapters are part of Barco's Nexxis solution, which provides users with uncompromised networked visualization for the digital operating room. The compact Nexxis AV-to-IP adapters offer simplicity and flexibility while maintaining the highest possible performance standards and fitness for use in demanding medical environments.

As a third generation device, the MNA-440 ENC SDI provides the full richness of the established Nexxis platform while:

- increasing future scalability
- improving ease of installation
- adding increased security performance
- reducing ecological footprint

Product specificaties

MNA-440 ENC SDI

Algemene specificaties

Videoconversie	Converts digital video signals to uncompressed IP streams
Verwerken	4096x2160p60 on a single 12G-SDI input or 4096x2160p60 on a quad 3G-SDI input or 1920x1080p60 on each of the two 3G-SDI input channels
Kleurdiepte	YCbCr 422: 8-bit / 10-bit
Latentie	Subframe
Beveiliging	AES 128 encryption of all video, data & control signals
Encodersysteem	N/A
Video-uitvoer	N/A
Video-ingang	3G/12G-SDI standard BNC connector on input channel 1 3G-SDI standard BNC connector on input channel 2, 3 and 4
Netwerkuitvoer	1x 4K/UHD uncompressed IP stream & 1x downscaled FHD IP stream of native 4K/UHD source Or 2x HD uncompressed IP stream
IP-connectiviteit	2x 10GE Fiber Optic Interface with SFP+ connector module
IP-standaarden	Zeroconf, IPv4, IGMP, DHCP, sRTP, sRTCP, 802.1q, AES 128b, HTTP(s)
USB	1x USB Type A
Audio	Headset/Stereo line out 15mm length compatible 3.5mm TRRS jack
Naleving	N/A
GPIO	1x GPI (1x camera trigger) via 15mm length compatible 3.5mm TRRS jack
Nexxis-integratie	Fully integrated in the Nexxis solution, compatible with MNA-1x0, MNA-240 and MNA-4x0 devices
NexxisPlus-integratie	N/A
PSU	External 12Vdc Medical Approved PSU, 100-240VAC 50-60Hz 60W with lockable connector at DC side
Energieverbruik	Maximum: 20W Typical: 13,6 W
Grootte	35 mm H x 103 mm W x 131 mm 1.4" H x 4.1" W x 5.2" D (+/-2 mm / 0.1")
Gewicht	0,4 kg (0.88 lbs)
Temperatuur	5°C to 40°C (41°F to 104°F)
Vochtigheid	Maximum 85%
Hoogte	700 hPa
Opslagcondities	Storage temperature: -20°C to 60°C (-4°F to 140°F) Storage relative humidity: 10% to 93% Storage altitude: 500 hPa
Akoestisch geluidsniveau	Typical 32dBA at 20°C at 1m
Montage	Versatile mounting bracket included
Certificeringen	-CB (IEC 60601-1) Informative report -CB (IEC 60950-1) -cRU, RU (cRUUs) -Demko -CE medical device class I -UKCA - BIS Registration, IS 13252 (part 1)
Normen	Medical Equipment: -IEC 60601-1:2005 + A1:2012 + A2:2020 -IEC 60601-1-6:2010 + A1:2013 + A2:2020 -IEC 60601-1-2: 2014+A1:2020 (Ed.4.1) -ANSI/AAMI ES 60601-1:2005 + A1:2012 + A2:2021 -CAN/CSA-C22.2 No.60601-1:08 + A1: 14 (Reaffirmed 2022) -EN 60601-1:2006 + A1:2013 + A2:2014 + A2:2021 -EN 60601-1-6:2010 + A1:2015 + A2:2021 -EN 60601-1-2:2015 + A1:2021 (Ed.4.1) -FCC class B -ICES-001 Level B ITE Equipment: -IEC 62368-1:2018 -EN IEC 62368-1:2020 + A11:2020 -IS 13252 (Part1): 2010
3D-video-ondersteuning	The following video formats are supported: 1920x1080p60Hz Line-interleaved 1920x1080i60Hz Line-interleaved Level B (vpid 0x8C) Dual-stream 1920x1080p60Hz (using first two-SDI input channels) UHD/4K60 3D Line interleaved half height: 3840/4096x1080 per view
Streamback	N/A

Laatst bijgewerkt: 17 Oct 2024

© 2024 Barco nv. Alle rechten voorbehouden. Gehele of gedeeltelijke reproductie zonder schriftelijke toestemming is verboden. Alle merknamen en productnamen zijn handelsmerken, geregistreerde handelsmerken of handelsnamen van hun respectieve houders. Als gevolg van voortdurende innovatie kunnen informatie en technische specificaties zonder voorafgaande kennisgeving worden gewijzigd. Controleer www.barco.com voor de nieuwste specificaties.