

# NRG-220

NexxisLive OR Remote Gateway



The NRG-220 is the gateway between your OR and remote participants when using NexxisLive for remote surgical collaboration. It collects video streams from the OR and sends these out via cloud software to remote participants anywhere in the world.

Each OR to be equipped with NexxisLive needs 1 NRG-220. After installation, no further physical adjustments are needed throughout its lifetime. Updates and new capabilities can simply be installed via the cloud with no interference to the hardware in the OR.

If the OR is also equipped with Nexxis OR-over-IP, the NRG-220 can be connected to the system via Barco's MNA-420 adapters.

**Product specificaties****NRG-220**

General specifications	
Hoogte	131.5 mm (5.18 in)
Breedte	220 mm (8.66 in)
Diepte	305 mm (12.01 in)
Gewicht	5.6 kg (12.35 lbs)
Vermogen	100V~ -240V~, 8A -4A, 50Hz / 60Hz
Energieverbruik	max. 500W
Geluidsniveau	max. 35db(A) at 25°C ambient temperature
Vochtigheid	5% to 80% non-condensing
Bedrijfstemperatuur	0°C to 40°C (32°F to 104°F)
Opslagtemperatuur	-20°C to 60°C (-4°F to 150°F)
Video-ingang	4x HDMI 1.4a Type A @ 1080p/60Hz (with HDCP support)
Video-uitgang	2x DisplayPort 1.2 1x HDMI 2.0a
Audio-ingang	1x Line-in/Mic-in Voltage: avg. 1.5 Vrms
Audio-uitgang	1x Line-out
USB	5x USB 3.1 (Type A) 2x USB 3.0 (Type A) 1x USB 3.1 (Type C)
Netwerkverbinding	2x Gbit (Intel I219LM, Intel I211 AT)

**Laatst bijgewerkt: 21 Jun 2023**

© 2018 Barco nv. Alle rechten voorbehouden. Gehele of gedeeltelijke reproductie zonder schriftelijke toestemming is verboden. Alle merknamen en productnamen zijn handelsmerken, geregistreerde handelsmerken of handelsnamen van hun respectieve houders. Vanwege voortdurende innovatie kunnen informatie en technische specificaties zonder voorafgaande kennisgeving worden gewijzigd. Raadpleeg [www.barco.com](http://www.barco.com) voor de meest recente specificaties.