

# Atlas

Compact mechanical system designed to house Poly-Silicon LCD projection systems with XGA or SXGA resolution and different screen types in 67" or 84" diagonal.



## 技术规格

## ATLAS

### 一般规格

电源	95-230 VAC ± 10%, 50-60 Hz
亮度均匀性	> 95 %
兼容性	Barco's Atlas integrates with the existing network environment and video sources via BARCO's graphical control units: EOS Compact, Power and Ultra, Hydra and Visu+.
对比度	250:1
尺寸结构	<p>Atlas 67" -XGA</p> <ul style="list-style-type: none"><li>· Width 1368 mm / 53.86 in.</li><li>· Height 1026 mm / 40.39 in.</li><li>· Footprint 753 mm / 29.65 in.</li><li>· Depth 897 mm / 35.32 in.</li><li>· Socket height (min) 614 mm / 24.17 in.</li><li>· Socket height (max) 1288 mm / 50.7 in.</li><li>· Weight 108 kg / 238 lbs</li></ul> <p>Atlas 67" -SXGA</p> <ul style="list-style-type: none"><li>· Width 1335 mm / 52.56 in.</li><li>· Height 1068 mm / 42.05 in.</li><li>· Footprint 798 mm / 31.4 in.</li><li>· Depth 942 mm / 37.1 in.</li><li>· Socket height (min) 492 mm / 19.4 in.</li><li>· Socket height (max) 1288 mm / 50.7 in.</li><li>· Weight 108 kg / 239 lbs</li></ul> <p>Atlas 84" -XGA</p> <ul style="list-style-type: none"><li>· Width 1708 mm / 67.24 in.</li><li>· Height 1281 mm / 50.43 in.</li><li>· Footprint 1041 mm / 41 in.</li><li>· Depth 1186 mm / 46.68 in.</li><li>· Socket height (min) 486 mm / 19.13 in.</li><li>· Socket height (max) 1288 mm / 50.7 in.</li><li>· Weight 138 kg / 305 lbs</li></ul> <p>Atlas 84" -SXGA</p> <ul style="list-style-type: none"><li>· Width 1650 mm / 65 in.</li><li>· Height 1320 mm / 52 in.</li><li>· Footprint 1079 mm / 42.5 in.</li><li>· Depth 1225 mm / 48.2 in.</li><li>· Socket height (min) 366 mm / 14.4 in.</li><li>· Socket height (max) 1288 mm / 50.7 in.</li><li>· Weight 138 kg / 305 lbs</li></ul>
运行环境	<ul style="list-style-type: none"><li>· Operating temperature: 17 °C -27 °C or 62 °F -80 °F</li><li>· Humidity: recommended 40% -60%, non condensing</li></ul> <p>Typical for stitched screens. Consult download for more info on screen modules.</p>
灯泡	100 Watt lamp Operation time 8,000 hours (average)
液晶面板	<ul style="list-style-type: none"><li>· XGA with 3-panel Poly-Silicon LCD, 4:3</li><li>· SXGA with 3-panel Poly-Silicon LCD, 5:4</li></ul>
亮度	Atlas 67" XGA -130 cd/m <sup>2</sup>   38 ftL Atlas 67" SXGA -110 cd/m <sup>2</sup>   32 ftL Atlas 84" XGA - 262 cd/m <sup>2</sup>   77 ftL Atlas 84" SXGA -220 cd/m <sup>2</sup>   65 ftL
亮度	XGA -500 lumens SXGA -600 lumens
可选	All projector settings are accessible through Barco's wall management software. Full features of this software can be viewed under this website 'Application software'
功率消耗	XGA resolution -140 W SXGA resolution -220 W
分辨率	XGA -1024x768 pixels SXGA -1280x1024 pixels depending on the projector, screen type and size used
屏幕尺寸	<ul style="list-style-type: none"><li>· 67" or 84" diagonally</li><li>· High gain screens for high brightness and high contrast black screens for wide viewing angles</li><li>· Other screens on request</li><li>· Download the brochure for more info on the principles and technologies</li></ul>

生成于: 09 Jul 2024

© 2024 巴可公司。保留所有权利。未经书面许可, 禁止全部或部分复制。所有品牌名称和产品名称均为其各自持有者的商标、注册商标或商号。由于不断创新, 信息和技术规格如有变更, 恕不另行通知。请查看[www.barco.com.cn](http://www.barco.com.cn)以了解最新规格。