

XLM H25

The ultimate high-brightness projector



Barco's XLM H25 projector is the ultimate high-brightness projector available on the market today. As the first DLPTM projector with a native wide-screen aspect ratio, native 2048 x 1080 resolution and light output of 28 000 center lumen, the XLM H25 projector is ideally suited to ultra wide-screen projections.

With its functional design, fully sealed DMD engine and adjustable convergence system, the XLM H25 projector is purpose built to work around the clock, making it ideal for use in the demanding rental & staging and large events markets.

Specifiche tecniche**XLM H25**

Specifiche generali	
Emissione luminosa	28000 Center Lumen
Risoluzione	2048 x 1080 (native)
Uniformità della luminosità	> 80% for the total screen
Rapporto di contrasto	1600 : 1 (full field) High contrast mode: Available with special lenses
Display	3 Chip DLP DC2K (resolution of 2048 x 1080 pixels (aspect ratio 1.89:1)).
Caratteristiche	<ul style="list-style-type: none"> ■ Advanced multi windowing ■ Seamless switching with effects ■ Standard light shutter ■ Rigging point ■ Carrying handle ■ Electronic tilt ■ High contrast mode ■ P7 color processing
PIP (Picture-In-Picture)	Up to 4 sources simultaneous (with alpha blending; z-order)
Ingressi	Modular inputs Standard: <ul style="list-style-type: none"> ■ 1x DVI ■ 1x SDI ■ 1x HD-SDI (all + loop through) ■ 1x RGB Analogue (up to UXGA) Optional: <ul style="list-style-type: none"> ■ 1x composite video/S-Video ■ 1x RGB/YUV (both + loop through)
Uscite	DB15 out (2048 x 1080 50/60 HZ)
Comunicazione	· 1x RS-232C IN (D-9 connector) · 1x RS-232C OUT (D-9 connector) · 1x RS-232C IN (XLR connector) · 1x 2way prop. protocol to Rugged remote (5 pins XLR connector) · 2x prop. protocol (RJ45 connector) · mini-jack for wired remote control
Compatibilità	· All current video sources (PAL, SECAM, NTSC) in Composite, S-VHS, Component or RGB formats · All currently proposed HDTV, extended and improved television standards (1080i; 720p) · All computer graphics formats from VGA, SVGA, XGA, SXGA,full HD to UXGA · Most Macintosh computers · Electronic workstations with a resolution up to 1600 x 1200 pixels at 75 Hz · Most computer sources with a pixel clock up to 200 MHz · DVI sources up to DC2K (2048x1080)
Compatibilità sorgente ingresso	max. input: up to 2048 x 1080 and 1600 x 1200
Dimensioni schermo	From 1-16m and higher / 3-52ft.recommended
Frequenze di scansione	Pixel clock >162Mhz (UXGA 60hz)
Connessione in rete	Standard (10/100 base-T; 2 ports; internal HUB)
Server per visualizzazione integrato	Ethernet control standard remote control projector over ethernet via Projector Toolset
Temperatura ambiente	Max 35°C (95°F)
Lampada	6.0 kW Xenon Lamp warranty: 750 hrs
Ottiche	Fixed focal lenses Lens Order nr XLD 1.0 R9852950 Zoom lenses Lens Order nr XLD 1.45 -1.8 R9852090 XLD 1.8 -2.4 R9852092 XLD 2.2 -3.0 R9852094 XLD 2.8 -5.5 R9852100 XLD 5.5 -8.5 R9852920

Specifiche tecniche**XLM H25**

Spostamento obiettivo	Vertical: -10% to +110% Horizontal: -50% to +50% (small differences occur per lens type)
Encoder obiettivo	On zoom and focus (with XLD lenses)
Rapporto di proiezione	Fixed focal lenses Lens Throw ratio XLD 1.0 1.0 Zoom lenses Lens Throw ratio XLD 1.45 -1.8 1.45 -1.80 XLD 1.8 -2.4 1.80 -2.40 XLD 2.2 -3.0 2.20 -3.00 XLD 2.8 -5.5 2.80 -5.50 XLD 5.5 -8.5 5.50 -8.50
ScenergiX	Standard horizontal and vertical electronic edge blending
Elemento centrale DLP™ sigillato	Standard
Filtri polvere	Metal filters
Livello di rumore	64 dBA (at 40°C)
Tensione di alimentazione	3 x 400 V + N or 3 x 220 V
Consumo energetico	8000 W
Dissipazione alimentazione	max 23906 BTU/h
Alimentazione CA	190V -255V (50 Hz -60Hz)
Peso	180 kg (400 lbs)
Dimensioni:	WxLxH 810 x 1563 x 631 mm (31.9 x 61.5 x 24.8 inch)
Norme di sicurezza	Compliant with UL1950 and EN60950
Interferenza elettromagnetica	Complies with FCC rules & regulations, part 15 Class A and CE EN55022 Class A
Informazioni per ordini	R9010100 (Projector incl. 4 inputs) R9010101 (Projector incl. 1 DVI) R9852410 (Spare Lamp) Fixed focal lenses Lens Order nr XLD 1.0 R9852950 Zoom lenses Lens Order nr XLD 1.45 -1.8 R9852090 XLD 1.8 -2.4 R9852092 XLD 2.2 -3.0 R9852094 XLD 2.8 -5.5 R9852100 XLD 5.5 -8.5 R9852920

Generato il: 15 Mar 2023

Le informazioni e i dati forniti riguardano l'apparecchiatura descritta. Tuttavia ogni singolo articolo è soggetto a modifiche senza preavviso.
 L'ultima versione di questo opuscolo è disponibile all'indirizzo www.barco.com.