

MNA-240 decoder

4K IP-to-AV adapter for the OR and Hybrid OR



- AV-to-IP and IP-to-AV conversion
- Up to 4K resolution
- Medical-grade

The MNA-240 decoder converts RAW IP packets into DVI video signals and other signals such as audio and USB. End-to-end latency is amazingly short and is guaranteed not to exceed a single frame (< 15 ms). The video streams that are distributed over the Nexxis network can go up to a resolution of 4K.

- IP-to-AV conversion at the endpoint
- Seamless integration with Barco's 4K surgical displays
- Support for non-video traffic (e.g. keyboard, mouse and audio) via USB connectivity
- Easy integration via central API provided by the Nexxis OR Management Suite NMS
- Quad-view video composition
- Streaming of FHD and UHD video composition into the network
- 4K video output
- Quad-view composition with up to 4 FHD video streams
- Network stream-back of FHD video composition
- 4K Transcoding enabled by SW license
- WorkSpot functionality enabled by SW license
- Nexxis Plug&Play via NMS
- Provides advanced image processing capabilities such as de-interlacing, scaling, overlaying, color conversion

Product specificaties

MNA-240 DECODER

General specifications

Videoconversie	Converts uncompressed IP-streams into Digital video signals
Verwerking	Up to 4096x2160@60Hz
Kleurdiepte	10 bits / color
Latentie	End-to-end: genlocked subframe; not genlocked two frames
Beveiliging	Decryption of AES 128 encrypted video, data & control signals
Video-uitgang	DisplayPort: 1 x DP 1.2 MST and SST, conversion to HDMI 2.0 via validated adapter cable DVI: 2 x DL-DVI
Netwerkuitvoer	<ul style="list-style-type: none">Compositor streamback mode: 1x FHD and 1x UHD video compositionTranscoding mode: Transcode 2 FHD (up to 1920x1080@60) raw streams simultaneously to 2 FHD H.264 streams or 1 UHD/4K (up to 4096x2160@60) stream to a UHD/4K half framerate H.264 stream (up to 4096x2160@30). In addition to the video stream(s), the MNA-240 can also transcode 2 raw audio streams into 2 AAC 128kbps encoded audio streams. <ul style="list-style-type: none">Note: Network output cannot be used in combination with video output.
IP-connectiviteit	2x 10GbE Fiber Optic Interface with SFP+ module
IP-normen	Zeroconf, IPv4, IGMP, DHCP, RTP, RTCP, 802.1q, AES 128b, HTTP(s)
USB	1x micro-USB 2.0 + 3x USB 2.0 type-A
Audio	Line-in, line-out, headphones-out and mic-in (mono) 3.5mm connector
Nexxis-integratie	Transcoding supported from Nexxis 1.15 onwards. The MNA-240 decoder is compatible with MNA-1x0, MNA-240 and MNA-4x0 devices
Voeding	External 12V Medical Approved PSU, 100-240VAC 60W, locking connector at DC side
Energieverbruik	< 37 W at an ambient temperature of 25 °C
Grootte	38 mm H x 170 mm W x 170 mm D 1.5" H x 6.7" W x 6.7" D (+/-2 mm / 0.1")
Gewicht	1±0.01kg (2.20lbs)
Temperatuur	Operating: 0°C to 40°C (32°F to 104°F)
Vochtigheid	Max 85%
Opslag	Storage temperature: -20°C to 60°C (-4°F to 140°F) Storage Relative Humidity: 10% to 93% Altitude: minimum 500hPa
Geluidsniveau	Typical 32dBA at 20°C at 1m
Montage	Optional VESA adapter plate or 1U rack mount for 2 devices
Certificeringen	<ul style="list-style-type: none">CB (IEC 60601-1) Informative reportCB (IEC 60950-1)cRU, RU (cRUus)DemkoCE medical device class IUKCABIS Registration, IS 13252 (part 1)KCBSMIRCMEAC
Standaarden	<ul style="list-style-type: none">IEC 60601-1:2005 + Am1:2012IEC 60601-1-6:2010 + Am1:2013IEC 60601-1-2:2014 (ed4)ANSI/AAMI ES 60601-1: A1:2012 + C1:2009/(R)2012 + A2:2010/(R)2012CAN/CSA-C22.2 No.60601-1-14EN 60601-1:2006 + A1:2013 + A12:2014EN 60601-1-6:2010 + A1:2015EN 60601-1-2:2015 (ed4)FCC class BICES-001 Level B <p>ITE Equipment:</p> <ul style="list-style-type: none">IEC 60950-1:2005 + Am1:2009 + Am2:2013EN 60950-1:2006 + A11:2009 + A1:2010 + A12:2011IS 13252

Laatst bijgewerkt: 18 Sep 2024

© 2024 Barco nv. Alle rechten voorbehouden. Gehele of gedeeltelijke reproductie zonder schriftelijke toestemming is verboden. Alle merknamen en productnamen zijn handelsmerken, geregistreerde handelsmerken of handelsnamen van hun respectieve houders. Als gevolg van voortdurende innovatie kunnen informatie en technische specificaties zonder voorafgaande kennisgeving worden gewijzigd. Controleer www.barco.com voor de nieuwste specificaties.