

# MXRT-7400

PCIe display controller for triple-head diagnostic imaging



## One board, three monitors

With the high-performance MXRT-7400, you can drive three displays with just one PCIe slot. As such, the board is the perfect match for PACS workstations combining two diagnostic displays (or one seamless 'Fusion' display) with a third monitor for patient lists or 3D viewing applications. This 'all-in-one' approach saves space on the PC; it simplifies the installation; and it reduces power consumption.

## Ultra-fast data transfers

The MXRT-7400 display controller is compatible with the DisplayPort interface standard, which assures easy installation and ultra-fast and reliable data transfers.

## Flexible projection configurations

The MXRT-7400 display controller is available with Barco's Conference CloneView<sup>TM</sup> software, which enables accurate projection of medical images onto a large-screen display.

The software tool ensures effortless cloning, scaling, zooming and panning of medical images on the large screen, making Barco displays and controllers perfectly suited for use in teaching hospitals, auditoriums and (tele)conference rooms.

## Product specifications

## MXRT-7400

### General specifications

Bus compatibility	PCIe Gen2 x16
Power consumption	138 W
Form factor	281.29mm (L) x 98.53mm (H) single PCIe slot wide
Operating system	Windows 7 -32/64-bit Windows XP -32/64-bit
Platforms	Intel® and AMD architectures
Power Connector	One 2x3 power connector
Graphics accelerator	ATI FirePro
Display memory	2 GB GDDR5
Memory interface	256-bit
Memory bandwidth	128 GB/s
Pixel depth	32-bit pixels (supports 8-bit and 10-bit per color channel)
Electrical standard	Dual Link DVI complying to v1.0 Display Port (DP) complying to v1.1a
Direct3D hardware support	Microsoft® DirectX v11.0, Vertex Shader 5.0, Pixel Shader 5.0
OpenGL hardware support	OpenGL 4.0
Connectors	1-DVI-I, 2-Display Port (DP)
Supported resolutions	Up to 5.8MP grayscale at full refresh rate (VGA at boot-up)
Approvals and compliance	FCC Part 15 Class B, CE EN 55022 Limit B, EN 55024, UL-60950-1, BMSI CNS, CISPR-22/24, IEC609050-1, VCCI, CSA C22.2, EU RoHS directive (2002/95/EC), Certificate of Information & Communication Equipment (Republic of Korea)
Operating temperature	0° to 60°C (32° to 140° F)
Connectivity	Single-link Display Port (DP) to DVI-I adaptor cable (2 adaptors are included) Dual-link Display Port (DP) to DVI-I adaptor available from Barco; Part Number K9305101

Last updated: 08 Jul 2024

© 2024 Barco nv. All rights reserved. Reproduction in whole or in part without written permission is prohibited. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Due to continued innovation, information and technical specifications are subject to change without prior notice. Please check [www.barco.com](http://www.barco.com) for the latest specifications.